

KMP Algorithm

2015.04.07

Jeehyeong Kim

Exact Matching Problem

- **Exact matching problem**

- Given a string P called the *pattern* and a longer string T called the *text*, the exact matching problem is to find all occurrences, if any, of pattern P in text T .
- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
T	b	b	a	b	a	x	a	b	a	b	a	y			input
P	a	b	a												input

Exact Matching Problem

- **Exact matching problem**

- Given a string P called the *pattern* and a longer string T called the *text*, the exact matching problem is to find all occurrences, if any, of pattern P in text T .
- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
T	b	b	a	b	a	x	a	b	a	b	a	y			input
P	a	b	a												input
			a	b	a										

Exact Matching Problem

- **Exact matching problem**

- Given a string P called the *pattern* and a longer string T called the *text*, the exact matching problem is to find all occurrences, if any, of pattern P in text T .
- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
T	b	b	a	b	a	x	a	b	a	b	a	y			input
P	a	b	a												input
			a	b	a										
							a	b	a						

Exact Matching Problem

- Exact matching problem**

- Given a string P called the *pattern* and a longer string T called the *text*, the exact matching problem is to find all occurrences, if any, of pattern P in text T .
- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
T	b	b	a	b	a	x	a	b	a	b	a	y			input
P	a	b	a												input
			a	b	a										
							a	b	a						
									a	b	a				

- Note that two occurrences of P may overlap

The Knuth-Morris-Pratt Algorithm

- **Naïve algorithm**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	d	a	b	c	b	d	a						
<i>P</i>	a	b	c												match at 1

The Knuth-Morris-Pratt Algorithm

- **Naïve algorithm**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	d	a	b	c	b	d	a						
<i>P</i>	a	b	c												match at 2

The Knuth-Morris-Pratt Algorithm

- **Naïve algorithm**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	d	a	b	c	b	d	a						
<i>P</i>	a	b	c												mismatch at 3

The Knuth-Morris-Pratt Algorithm

- **Naïve algorithm**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	d	a	b	c	b	d	a						
<i>P</i>		a	b	c											Shift 1 place

The Knuth-Morris-Pratt Algorithm

- **Naïve algorithm**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	d	a	b	c	b	d	a						
<i>P</i>		a	b	c											Mismatch at 2

Begin comparing again from the left end of *P*

The Knuth-Morris-Pratt Algorithm

- **Naïve algorithm**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	d	a	b	c	b	d	a						
<i>P</i>			a	b	c										Shift 1 place

The Knuth-Morris-Pratt Algorithm

- **Naïve algorithm**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	d	a	b	c	b	d	a						
<i>P</i>			a	b	c										Mismatch at 3

The Knuth-Morris-Pratt Algorithm

- **Naïve algorithm**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	d	a	b	c	b	d	a						
<i>P</i>				a	b	c	d								Shift 1 place

The Knuth-Morris-Pratt Algorithm

- **Naïve algorithm**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	d	a	b	c	b	d	a						
<i>P</i>				a	b	c									match at 4

The Knuth-Morris-Pratt Algorithm

- **Naïve algorithm**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	d	a	b	c	b	d	a						
<i>P</i>				a	b	c									match at 5

The Knuth-Morris-Pratt Algorithm

- **Naïve algorithm**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	d	a	b	c	b	d	a						
<i>P</i>				a	b	c									match at 6

P occurs at position 4 of *T*

The Knuth-Morris-Pratt Algorithm

- **Naïve algorithm**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	d	a	b	c	b	d	a						
<i>P</i>					a	b	c								Shift 1 place

The Knuth-Morris-Pratt Algorithm

- **Naïve algorithm**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	d	a	b	c	b	d	a						
<i>P</i>					a	b	c								Mismatch at 5

Begin comparing again from the left end of *P*

The Knuth-Morris-Pratt Algorithm

- **Naïve algorithm**
 - Complexity
 - $O(mn)$
 - The length of $T = n$
 - The length of $P = m$
 - $O(m+n) \rightarrow$ KMP algorithm

The KMP algorithm

- **The KMP shift idea**
 - Make **larger shifts** than the naïve algorithm
 - The number of **comparisons are smaller** than the naïve algorithm
 - After a shift, the left-most characters of P are guaranteed to match their counterparts in T

The KMP algorithm

- **The KMP shift idea**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	c	x	a	b	c	a	b	c	x	a			
<i>P</i>	a	b	c	x	a	b	c	d	e						mismatch at 8

The KMP algorithm

- **The KMP shift idea**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	c	x	a	b	c	a	b	c	x	a			
<i>P</i>	a	b	c	x	a	b	c	d	e						mismatch at 8
Naïve		a	b	c	x	a	b	c	d	e					Shift 1 place

The KMP algorithm

- **The KMP shift idea**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	c	x	a	b	c	a	b	c	x	a			
<i>P</i>	a	b	c	x	a	b	c	d	e						mismatch at 8
Naïve			a	b	c	x	a	b	c	d	e				Shift 1 place

The KMP algorithm

- **The KMP shift idea**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	c	x	a	b	c	a	b	c	x	a			
<i>P</i>	a	b	c	x	a	b	c	d	e						mismatch at 8
Naïve				a	b	c	x	a	b	c	d	e			Shift 1 place

The KMP algorithm

- **The KMP shift idea**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	c	x	a	b	c	a	b	c	x	a			
<i>P</i>	a	b	c	x	a	b	c	d	e						mismatch at 8
Naïve					a	b	c	x	a	b	c	d	e		Shift 1 place

- Need to shift and compare 4 times
 - to find the start position of occurrences of P in T
- Have to compare the “already matched” part again

The KMP algorithm

- **The KMP shift idea**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	c	x	a	b	c	a	b	c	x	a			
<i>P</i>	a	b	c	x	a	b	c	d	e						mismatch at 8
Naïve		a	b	c	x	a	b	c	d	e					
KMP					a	b	c	x	a	b	c	d	e		Shift 4 places

- KMP algorithm can shift *P* by four places without passing over any occurrences of *P* in *T*

The KMP algorithm

- **The KMP shift idea**

- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	c	x	a	b	c	a	b	c	x	a			
<i>P</i>	a	b	c	x	a	b	c	d	e						mismatch at 8
Naïve		a	b	c	x	a	b	c	d	e					
KMP					a	b	c	x	a	b	c	d	e		Shift 4 places

- KMP algorithm can shift *P* by four places without passing over any occurrences of *P* in *T*
- Starts comparing at position 8
 - which was the “mismatched” position
 - Don’t have to compare the “already matched” part again.

The KMP algorithm


- **The KMP shift idea**

- For example


	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
<i>T</i>	a	b	c	x	a	b	c	a	b	c	x	a			
<i>P</i>	a	b	c	x	a	b	c	d	e						mismatch at 8
Naïve		a	b	c	x	a	b	c	d	e					
KMP					a	b	c	x	a	b	c	d	e		Shift 4 places

- KMP algorithm can shift *P* by four places without passing over any occurrences of *P* in *T*
- Starts comparing at position 8
 - which was the “mismatched” position
 - Don’t have to compare the “already matched” part again.


The KMP algorithm



The KMP algorithm



The KMP algorithm



\therefore Suffix of *P* should be the largest one

The KMP algorithm

- **The Definition of $sp_i(P)$**

For each position of i in pattern P , define $sp_i(P)$ to be the length of the longest proper suffix of $P[1..i]$ that matches a prefix of P .

- $sp_i(P)$ is the length of the longest proper substring of $P[1..i]$ that ends at i and matches a prefix of P .

The KMP algorithm

- **The Definition of $sp_i(P)$**

- $sp_i(P)$ is the length of the longest proper substring of $P[1 \dots i]$ that ends at i and matches a prefix of P .
- For example $P = aaabcaabe$, $sp_6 = ??$

	1	2	3	4	5	6	7	8	9	10	11	
P	a	a	b	c	a	a	b	e				

The KMP algorithm

- **The Definition of $sp_i(P)$**

- $sp_i(P)$ is the length of the longest proper substring of $P[1 \dots i]$ that ends at i and matches a prefix of P .
- For example $P = aaabcaabe$, $sp_6 = ??$

	1	2	3	4	5	6	<i>i</i>	7	8	9	10	11	
<i>P</i>	a	a	b	c	a	a		b	e				
				≠									
		a	a	b	c	a							Mismatch

The KMP algorithm

- **The Definition of $sp_i(P)$**

- $sp_i(P)$ is the length of the longest proper substring of $P[1 \dots i]$ that ends at i and matches a prefix of P .
- For example $P = aaabcaabe$, $sp_6 = ??$

	1	2	3	4	5	6	<i>i</i>	7	8	9	10	11	
<i>P</i>	a	a	b	c	a	a		b	e				
		a	a	b	c	a							
													Mismatch

The KMP algorithm

- **The Definition of $sp_i(P)$**

- $sp_i(P)$ is the length of the longest proper substring of $P[1 \dots i]$ that ends at i and matches a prefix of P .
- For example $P = aaabcaabe$, $sp_6 = ??$

		1	2	3	4	5	6	<i>i</i>	7	8	9	10	11	
P		a	a	b	c	a	a		b	e				
			a	a	b	c	a							Mismatch
			a	a	b	c								Mismatch

The KMP algorithm

- **The Definition of $sp_i(P)$**

- $sp_i(P)$ is the length of the longest proper substring of $P[1 \dots i]$ that ends at i and matches a prefix of P .
- For example $P = aaabcaabe$, $sp_6 = ??$

		1	2	3	4	5	6	7	8	9	10	11	
P		a	a	b	c	a	a	b	e				
			a	a	b	c	a						Mismatch
				a	a	b	c						Mismatch

The KMP algorithm

- **The Definition of $sp_i(P)$**

- $sp_i(P)$ is the length of the longest proper substring of $P[1 \dots i]$ that ends at i and matches a prefix of P .
- For example $P = aaabcaabe$, $sp_6 = ??$

						<i>i</i>						
	1	2	3	4	5	6	7	8	9	10	11	
P	a	a	b	c	a	a	b	e				
		a	a	b	a	a						Mismatch
			a	a	b	c						Mismatch
				a	a	b						Mismatch

The KMP algorithm

- The Definition of $sp_i(P)$**

- $sp_i(P)$ is the length of the longest proper substring of $P[1 \dots i]$ that ends at i and matches a prefix of P .
- For example $P = aaabcaabe$, $sp_6 = ??$

						<i>i</i>						
	1	2	3	4	5	6	7	8	9	10	11	
P	a	a	b	c	a	a	b	e				
		a	a	b	c	a						Mismatch
			a	a	b	c						Mismatch
				a	a	b						Mismatch

The KMP algorithm

- The Definition of $sp_i(P)$**

- $sp_i(P)$ is the length of the longest proper substring of $P[1 \dots i]$ that ends at i and matches a prefix of P .
- For example $P = aaabcaabe$, $sp_6 = ??$

						<i>i</i>						
	1	2	3	4	5	6	7	8	9	10	11	
P	a	a	b	c	a	a	b	e				
		a	a	b	c	a						Mismatch
			a	a	b	= c						Mismatch
				a	a	b						Mismatch
					a	a						Match

The KMP algorithm

- The Definition of $sp_i(P)$**

- $sp_i(P)$ is the length of the longest proper substring of $P[1 \dots i]$ that ends at i and matches a prefix of P .
- For example $P = aaabcaabe$, $sp_6 = ??$

						<i>i</i>						
	1	2	3	4	5	6	7	8	9	10	11	
P	a	a	b	c	a	a	b	e				
		a	a	b	c	a						Mismatch
			a	a	b	c						Mismatch
				a	a	b						Mismatch
					a	a						Match

The KMP algorithm

- The Definition of $sp_i(P)$**

- $sp_i(P)$ is the length of the longest proper substring of $P[1 \dots i]$ that ends at i and matches a prefix of P .
- For example $P = aaabcaabe$, $sp_6 = ??$

						<i>i</i>						
	1	2	3	4	5	6	7	8	9	10	11	
P	a	a	b	c	a	a	b	e				
		a	a	b	c	a						Mismatch
			a	a	b	e						Mismatch
				a	a	b						Mismatch
					a	a						Match
						a						Match

The KMP algorithm

- **The Definition of $sp_i(P)$**

- $sp_i(P)$ is the length of the longest proper substring of $P[1 \dots i]$ that ends at i and matches a prefix of P .

- For example $P = aaabcaabe$

- So, $sp_6 = 2$

	1	2	3	4	5	6	7	8	9	10	11	
P	a	a	b	c	a	a	b	e				
		a	a	b	c	a						Mismatch
			a	a	b	<u>a</u>						Mismatch
				a	a	b						Mismatch
					a	a						Match

The KMP algorithm

- Weakness of sp_i

- Shift using sp_i value

- ex) $P = a\ b\ c\ a\ b\ d\ a\ b\ c\ a\ b\ d$

$sp_{11} = 5$

		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
	T	a	b	c	a	b	d	a	b	c	a	b	c	a	b	d	...
sp_i	P	a	b	c	a	b	d	a	b	c	a	b	d				
	T	a	b	c	a	b	d	a	b	c	a	b	c	a	b	d	...
	P							a	b	c	a	b	d				

There's an mismatch at position 12. We can shift 6 character. But, the same kind of mismatch (comparing c with d) occurs at the same position 12.

The KMP algorithm

- **The Definition of $sp'_i(P)$**

For each position of i in pattern P , define $sp'_i(P)$ to be the length of the longest proper suffix of $P[1 \dots i]$ that matches a prefix of P ,

with the character $P(i+1) \neq P(sp'_i+1)$

- means right character of matched prefix and suffix are not equal.

The KMP algorithm

- The Definition of $sp'_i(P)$

- with the character $P(i+1) \neq P(sp'_i+1)$

- For example $P = aabcaabe$, $sp_6 = 2$, $sp'_6 = ??$

			sp'_i	sp'_i+1		i	$i+1$							
	1	2	3	4	5	6	7	8	9	10	11			
P	a	a	b	c	a	a	b	e						
		a	a	b	c	a								Mismatch
			a	a	b	c								Mismatch
				a	a	b								Mismatch
					a	a	b							Match
						a	a							Match

The KMP algorithm

- **The Definition of $sp'_i(P)$**

- with the character $P(i+1) \neq P(sp'_i+1)$

- For example $P = aabcaabe$, $sp_6 = 2$, $sp'_6 = ??$

		sp'_i		sp'_i+1			i	$i+1$							
	1	2	3	4	5	6	7	8	9	10	11				
P	a	a	b	c	a	a	b	e							
		a	a	b	c	a									Mismatch
			a	a	b	c									Mismatch
				a	a	b									Mismatch
					a	a	b								Match
						a	a								Match

The KMP algorithm

- **The Definition of $sp'_i(P)$**

- with the character $P(i+1) \neq P(sp'_i+1)$

- For example $P = aabcaabe$, $sp_6 = 2$, $sp'_6 = ??$

		sp'_i	sp'_i+1				i	$i+1$						
	1	2	3	4	5	6	7	8	9	10	11			
P	a	a	b	c	a	a	b	e						
		a	a	b	c	a								Mismatch
			a	a	b	c								Mismatch
				a	a	b								Mismatch
					a	a	b							Match
						a	a							Match

The KMP algorithm

- **The Definition of $sp'_i(P)$**

- with the character $P(i+1) \neq P(sp'_i+1)$

- For example $P = aabcaabe$, $sp_6 = 2$, $sp'_6 = ??$

		sp'_i	sp'_i+1				i	$i+1$						
	1	2	3	4	5	6	7	8	9	10	11			
P	a	a	b	c	a	a	b	e						
		a	a	b	c	a							Mismatch	
			a	a	b	c							Mismatch	
				a	a	b							Mismatch	
					a	a	b						Match	
						a	a						Match	

The KMP algorithm

- **The Definition of $sp'_i(P)$**

- with the character $P(i+1) \neq P(sp'_i+1)$

- For example $P = aabcaabe$, $sp_6 = 2, sp'_6 = 1$

		sp'_i	sp'_i+1				i	$i+1$						
	1	2	3	4	5	6	7	8	9	10	11			
P	a	a	b	c	a	a	b	e						
		a	a	b	c	a								Mismatch
			a	a	b	c								Mismatch
				a	a	b								Mismatch
					a	a	b							Match
						a	a							Match

The KMP algorithm

- Weakness of sp_i

- Shift using sp_i value

- ex) $P = a\ b\ c\ a\ b\ d\ a\ b\ c\ a\ b\ d$

$sp_{11} = 5$

$sp'_{11} = ??$

		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
	T	a	b	c	a	b	d	a	b	c	a	b	c	a	b	d	...
sp_i	P	a	b	c	a	b	d	a	b	c	a	b	d				
	T	a	b	c	a	b	d	a	b	c	a	b	c	a	b	d	...
	P							a	b	c	a	b	d				

The KMP algorithm

- Weakness of sp_i
 - Shift using sp'_i value
 - ex) $P = a\ b\ c\ a\ b\ d\ a\ b\ c\ a\ b\ d$

$$sp_{11} = 5$$

$$sp'_{11} = 2$$

		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
sp'_i	T	a	b	c	a	b	d	a	b	c	a	b	c	a	b	d	...
	P	a	b	c	a	b	d	a	b	c	a	b	d				
	T	a	b	c	a	b	d	a	b	c	a	b	c	a	b	d	...
	P										a	b	c	a	b	d	...

$sp'_{11} = 2$, We can **shift more characters** than when we use sp_{11} value. And the next character is not the same character that was mismatched. We don't have to do the same comparison again.

The KMP algorithm

- **Theorem 2.3.3 (Time Complexity)**

In the KMP method, the number of character comparisons is at most $2n$.

Time complexity of KMP

- the total number of character comparisons =
number of matches + number of mismatches
- For example

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
<i>T</i>	x	y	a	b	c	x	a	b	c	x	a	d	c	x	a	d	c	d	q	f	e	g
<i>P</i>			a	b	c	x	a	b	c	d	e											
compare			1	1	1	1	1	1	1	1												
Shift 4							a	b	c	x	a	b	c	d	e							
compare										1	1	1	1	1								
Shift 4											a	b	c	x	a	b	c	d	e			
compare														1	1							
Total compare			1	1	1	1	1	1	1	2	1	1	1	2	1							

Shift Rule

- **Proof**

- n : the length of T
- s : number of shifts

the total number of character comparisons =
number of matches + number of mismatches

1. The number of matches
➔ if character matches, never compare again (the number of matches = n)
2. The number of mismatches
➔ if character mismatches, shift occurs (the number of mismatches = s)

Shift Rule

- **Proof**

- n : the length of T
- s : number of shifts

the total number of character comparisons

$$= n + s$$



The number of shifts cannot
be larger than the length of T

$$\leq n + n$$


$$\leq 2n$$

The Original Preprocessing For KMP

- **The Preprocessing for KMP**
 - Compute $sp_i(P)$ for each position i
 - From $i = 2$ to $i = n$, ($sp_1 = 0$)
 - Inductively
$$sp_1 \rightarrow sp_2 \rightarrow sp_3 \rightarrow sp_4 \dots$$
 - To compute sp_i , assume that we know $sp_1, sp_2 \dots sp_{i-1}$

The Original Preprocessing For KMP

- How to compute sp_{i+1}




There are two cases :

- ① $P(i+1) = P(sp_i)+1$
- ② $P(i+1) \neq P(sp_i)+1$

The Original Preprocessing For KMP


① $P(sp_i)+1 = P(i+1)$



$$sp_{i+1} = sp_i + 1$$


The Original Preprocessing For KMP

② $P(sp_i)+1 \neq P(i+1)$ (the general case of computing sp_{i+1})




The Original Preprocessing For KMP


② $P(sp_i)+1 \neq P(i+1)$




The Original Preprocessing For KMP




The Original Preprocessing For KMP




The Original Preprocessing For KMP




The Original Preprocessing For KMP




The Original Preprocessing For KMP



The Original Preprocessing For KMP



The Original Preprocessing For KMP




The Original Preprocessing For KMP

- **Theorem 3.3.1 (Complexity)**

Algorithm SP finds all the $sp_i(P)$ values in $O(m)$ time, where m is the length of P

The Original Preprocessing For KMP

- time complexity



- If
 - ① $P(sp_i)+1 = P(i+1) \rightarrow O(1)$
 - ② $P(sp_i)+1 \neq P(i+1) \rightarrow$ depends on
the number of times sp_i jumps

The Original Preprocessing For KMP

- time complexity

	a	b	x	a	b	q	a	b	x	a	b	r	a	b	x	a	b	q	a	b	x	a	b	x
sp_i	0	0	0																					

The Original Preprocessing For KMP

- time complexity

	a	b	x	a	b	q	a	b	x	a	b	r	a	b	x	a	b	q	a	b	x	a	b	x
sp_i	0	0	0	1																				


The Original Preprocessing For KMP

- time complexity

	a	b	x	a	b	q	a	b	x	a	b	r	a	b	x	a	b	q	a	b	x	a	b	x
sp_i	0	0	0	1	2																			

The Original Preprocessing For KMP

- time complexity



The Original Preprocessing For KMP

- time complexity

	a	b	x	a	b	q	a	b	x	a	b	r	a	b	x	a	b	q	a	b	x	a	b	x
sp_i	0	0	0	1	2	0	1																	

The Original Preprocessing For KMP

- time complexity

	a	b	x	a	b	q	a	b	x	a	b	r	a	b	x	a	b	q	a	b	x	a	b	x
sp_i	0	0	0	1	2	0	1	2																

The Original Preprocessing For KMP

- time complexity

	a	b	x	a	b	q	a	b	x	a	b	r	a	b	x	a	b	q	a	b	x	a	b	x
sp_i	0	0	0	1	2	0	1	2	3															

The Original Preprocessing For KMP

- time complexity

	a	b	x	a	b	q	a	b	x	a	b	r	a	b	x	a	b	q	a	b	x	a	b	x
sp_i	0	0	0	1	2	0	1	2	3	4														

The Original Preprocessing For KMP


- time complexity

	a	b	x	a	b	q	a	b	x	a	b	r	a	b	x	a	b	q	a	b	x	a	b	x
sp_i	0	0	0	1	2	0	1	2	3	4	5													

When the value of sp_i is increasing, it can only increase by 1
→ The value of sp_i can increase at most $m-1$.

The Original Preprocessing For KMP

- time complexity



The value of sp_i can decrease as large as the amount it has increased.

The Original Preprocessing For KMP

- time complexity

	a	b	x	a	b	q	a	b	x	a	b	r	a	b	x	a	b	q	a	b	x	a	b	x
sp_i	0	0	0	1	2	0	1	2	3	4	5	0	1	...										

The total value of sp_i can increase at most $m-1$ over the entire algorithm \rightarrow No matter how many times does sp_i decrease, the total amount that the value of sp_i can decrease is bounded by $m-1$ $\rightarrow O(m)$


The Original Preprocessing For KMP

- time complexity

If


$$\textcircled{1} P(sp_i)+1 = P(i+1) \rightarrow O(1) * m$$

$$\textcircled{2} P(sp_i)+1 \neq P(i+1) \rightarrow O(m)$$



The Original Preprocessing For KMP


- **How to compute sp'_i**
 - assume that we know the value sp_i



- ① $P(sp_i)+1 \neq P(i+1) \rightarrow sp'_i = sp_i$
- ② $P(sp_i)+1 = P(i+1) \rightarrow sp'_i = sp'_{sp_i}$


The Original Preprocessing For KMP

$$\textcircled{1} \ P(sp_i)+1 \neq P(i+1) \Rightarrow sp'_i = sp_i$$



The Original Preprocessing For KMP

$$\textcircled{1} P(sp_i)+1 \neq P(i+1) \rightarrow sp'_i = sp_i$$




according to the definition of sp'_i

$$sp'_i = sp_i$$


The Original Preprocessing For KMP

$$\textcircled{2} P(sp_i)+1 = P(i+1) \rightarrow sp'_i = sp'_{sp_i}$$




The Original Preprocessing For KMP

$$\textcircled{2} P(sp_i)+1 = P(i+1) \rightarrow sp'_i = sp'_{sp_i}$$




The Original Preprocessing For KMP

② $P(sp_i)+1 = P(i+1) \rightarrow sp'_i = sp'_{sp_i}$



The Original Preprocessing For KMP

② $P(sp_i)+1 = P(i+1) \rightarrow sp'_i = sp'_{sp_i}$



Satisfies the definition of sp'_i
 $sp'_i = sp'_{sp_i}$

The Original Preprocessing For KMP

- time complexity

The time used to compute sp_i

$$\textcircled{1} P(sp_i)+1 \neq P(i+1) \rightarrow sp'_i = sp_i$$

$$\textcircled{2} P(sp_i)+1 = P(i+1) \rightarrow sp'_i = sp'_{sp_i}$$

$$O(m)$$

$$O(1) * m$$

$$O(1) * m$$

$$O(m)$$