Session 1.2a Strength, Weakness, Modeling Standards and Processing Strategies of Space Geodetic Techniques

Impact of GLONASS in a rigorous combination with GPS

M. Fritsche[1], C. Rodriguez-Solano[2], P. Steigenberger[2], K. Sosnica[3], K. Wang[4], R. Dietrich[1], U. Hugentobler[2], R. Dach[3], M. Rothacher[4]

[1] Technische Universität Dresden, Germany
[2] Technische Universität München, Germany
[3] AIUB, Universität Bern, Switzerland
[4] Eidgenössische Technische Hochschule Zürich, Switzerland

IAG Scientific Assembly 2013, Potsdam 01-06.09.2013

Outline

Observation data, modeling, processing scheme

Results from a combined GNSS processing

- Station coordinates/velocities
- Orbit validation
- Satellite clocks

Conclusions

Observation data and modeling

- Reprocessing starting on observation level: 1994 - 2011
- 340 GNSS stations in total (140 with GLONASS observation), 70 SLR stations
- GLONASS included since 01. January 2002
- GPS-only, GLONASS-only and GPS+GLONASS-combined solutions
- SLR: range residuals w.r.t. to microwave-based GNSS satellite orbits
- Processing of 24-hour epoch for clock solutions
- Major modelling aspects

Terrestrial reference frame:	ITRF2008/IGS08
GNSS antenna phase center:	IGS08.atx
Atmospheric tidal loading:	S_1+S_2 tides (Ray and Ponte, 2003)
Atmospheric+oceanic non-tidal loading:	GRACE AOD1B (RL04)
Radiation pressure for GNSS satellites:	Earth albedo included

Station network



□GPS+GLONASS ● GPS-only ♦ SLR

Number of processed stations and satellites



GPS

GPS+GLONASS

GPS

GLONASS

System-specific number of observation days

Relative contribution in terms of time series length

GPS



GLONASS



Terrestrial Reference Frame (TRF)



IGS08 w.r.t.	Translation [mm] / Translation rates [mm/y]			Scale [ppb]/ Scale rate [ppb/y]
	X	Y	Z	
GPS-only	-4.3	-7.0	-2.8	-0.41
	-1.1	+1.3	+0.7	-0.02
GPS+GLONASS	-4.1	-6.7	-2.6	-0.42
	-1.0	+1.2	+0.7	-0.02

TRF: Time series analysis

Input: daily position time series

Functional model: annual, semi-annual, draconitic harmonics

Stochastic model: combined white + flicker noise model

GPS+GLONASS (vertical components) GPS-only







ORB: Transformation of satellite positions



ORB: Overlaps from 1-day arcs



GPS:

GPS-only

GPS+GLONASS



GLONASS:

GLONASS-only

GPS+GLONASS

ORB: Overlaps from 3-day arcs



GPS:

GPS-only

GPS+GLONASS



GLONASS:

GLONASS-only

GPS+GLONASS

ORB: SLR range residuals



GNSS satellite clocks (30sec)

Modified Allan Deviation (MDEV) from a 5-day interval in 2008

GPS



(missing epochs < 5%)

GLONASS



(missing epochs < 15%)

PPP Phase Residuals



Conclusions

- Impact of including GLONASS on TRF parameters
  - no systematic effect for linear TRF parameters
  - slight reduction of daily position repeatabilities

- Combination with GPS and 3-day arc length significantly improves GLONASS orbits

- Conventional consideration of albedo modeling required

- Study of remaining model errors based on precise clocks products (yaw maneuvers modeling for both GNSS)

Acknowledgement

The authors acknowledge the support provided by the German Research Foundation (DFG) and the Swiss National Science Foundation (SNSF).