**#0151**

# ENGINE-OIL SUPPLEMENT




## 01 // OUTSTANDING FEATURES

- Specially formulated to reduce friction and increase the lubricating power of oil.
- Protects new engines during break-in and start up.
- Dispersants and detergents to help prevent sludge buildup.
- Can be used in all types of internal-combustion engines.

## 02 // DESCRIPTION

Scientifically formulated to increase performance by reducing friction and wear. MOC® Engine-Oil Supplement contains dispersants and detergents to help prevent sludge buildup. This reduction in friction can protect new engines during break-in and startups. It may be used in all internal combustion engines, including rotary and diesel.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Oil** |
| Color | N/A | **Dark Brown** |
| Odor | N/A | **Petroleum** |
| Density (g/mL) | D4052 | **0.86** |
| Density, U.S. (lbs/gal), calculated | N/A | **7.18** |
| Viscosity, cSt @ 40°C | D445 | **25** |
| Viscosity, cSt @ 100°C | D445 | **5** |
| Boiling Point (°F) | N/A | **>400** |
| Flash Point(°F) (based on components) | N/A | **>248** |
| Viscosity Index | N/A | **129** |

## 04 // APPLICATION

Add entire contents to crankcase at each oil change and between changes, as needed. Treats 4 to 6 quarts of oil.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **8 oz.** | 24 | 14 lbs. |