**#0611**

# PREMIUM SYNTHETIC ATF - RED




## 01 // OUTSTANDING FEATURES

- Superior oxidation stability.
- Very good cold weather performance.
- Improved shear stability.
- Conditions seals and hoses.

## 02 // DESCRIPTION

Formulated to provide wear and rust protection, lubricity, good flow properties, excellent high and low temperature performance as well as stringent anti-shudder capability. This fluid is suitable for use in Ford, General Motors, Chrysler ATF+4, Allison C4, Volkswagen #G052 162A2, Audi, Volvo, Toyota (T-IV), Lexus, Honda Z1, Hyundai, Nissan (Matic-J), Infiniti, BMW, Mercedes Benz, and Jaguar.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Oil** |
| Color | N/A | **Red** |
| Odor | N/A | **Petroleum** |
| Specific Gravity @ 68°F | D4052 | **~0.85** |
| Density, U.S. (lbs/gal) (Calculated) | N/A | **~7.09** |
| Viscosity, cSt @ 100°C | D445 | **~7** |
| Viscosity, cSt @ 40°C | D445 | **~38** |
| Viscosity Index | D 2270 | **> 147** |

## 04 // APPLICATION

MOC® Premium Synthetic ATF (#0611) must be used according to equipment manufacturer's recommendations. Do not use in transmissions which require CVT or Dexron VI fluid.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **1 gal.** | 4 Bottles | 30 lbs. |
| **3 gal.** | 2 Bottles | 46 lbs. |