**AUTOMOTIVE CLEANER**
PRODUCT PERFORMANCE & DATA SHEET

**#2108**

# SURFACE CERAMIC SPRAY




## 01 // OUTSTANDING FEATURES

- Sio2 ceramic detailing spray
- Safe for all vehicle surfaces
- Enhances gloss, depth, shine
- Extends the protection of waxes sealants

## 02 // DESCRIPTION

A specialized blend of lubricants, anti-static, and ceramic agents that clean and seal automotive painted surfaces, creating a mirror reflection and intense crystalline shine. SURFACE™ guards against harmful UV rays and environmental contaminants such brake dust, dirt, dust, industrial fallout, and bird droppings.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Liquid** |
| Color | N/A | **Purple** |
| Odor | N/A | **Grape** |
| Density, U.S. (g/ml) @ 68°F | N/A | **.99 - 1.0** |
| Density, U.S. (lbs/gal) @ 68°F | N/A | **8.30 - 8.345** |
| pH | N/A | **5.8 - 7** |
| Flash Point (°C / °F) | N/A | **62 / 143.6** |
| Body Shop Safe | N/A | **No** |
| VOC Complaint | N/A | **Yes** |
| Biodegradable | N/A | **No** |

## 04 // APPLICATION

DIRECTIONS: to ensure an ideal bond, we recommend applying SURFACE ® to a clean, dry, and smooth surface. Spray SURFACE ® onto painted surfaces, one panel at a time. distribute evenly using a clean microfiber towel and buff to a smooth shiny surface. for vehicles already protected by ARMOUR ® ceramic coating use SURFACE ® to revitalize and extend shine and hydrophobic properties of ARMOUR ®

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **1.02 oz** | 12 | xx lbs. |