EXTERIOR CLEANER
PRODUCT PERFORMANCE & DATA SHEET

#4789

ULTRA WHEEL CLEANER



01 // OUTSTANDING FEATURES

- A powerful cleaner for all types of wheels.
- Quickly dissolves tough brake dust, dirt and grime.
- A great alternative to acid-based wheel cleaners.

Performance ratings // Concentration 8

02 // DESCRIPTION

A powerful cleaner designed to remove stubborn brake dust, grease, dirt and stains from wheels, rims, and hubcaps. Contains no acids. Use caution on aluminum, magnesium, or anodized wheels. Test on a small inconspicuous area before using on entire surface. Do not mix with other products as they may not be compatible and could result in unsatisfactory performance.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear**
Color Odor	N/A	**Green**
Density, U.S. (lbs/gal)	D4052	**1.09**
Density, U.S. (lbs/gal)	N/A	**9.06**
PH	N/A	**12.5 - 13.5**
Boiling Point	Based on Components	**≥ 0°C / 32 °F**
Flash Point	Based on Components	**> 99 °C / 210.2°F**
Body Shop Safe	N/A	**Yes**
VOC Compliant	N/A	**Yes**
Biodegradable	N/A	**No**

04 // APPLICATION

MIXING INSTRUCTIONS: Option 1: Dilution by proportioner. Remove cap, create a hole in the center of the cap or secure cap/draw tube assembly from MOC Recon Cabinet system. Place draw tube of the proportioner into the container. Set dilution ratio on proportioner to desired concentration. Operate proportioner per manufacturer's instructions. Option 2: Transfer entire contents to a clean empty 55-gallon drum. Fill drum with filtered water until full. Stir contents until uniform. Apply secondary label LB4736S to drum. Dilute further as needed for final use and concentration.

05 // PACKAGING

FILL	CASE QTY	CASE WT
5 gal	1 each	48.96 lbs