**#0156**

# POWER STEERING SERVICE SOLUTION - RED




## 01 // OUTSTANDING FEATURES

- Reduces friction that can wear out the pump, valves, and gears.
- Conditions seals and hoses to help prevent cracks and leaks.
- Helps extend system life by reducing wear on internal components.
- Helps reduce squeals and chatter due to foaming.
- Outstanding cold weather performance.

## 02 // DESCRIPTION

A fortified power-steering fluid blend that is used in conjunction with a MOC® Power-Steering Fluid Exchanger. The formulation utilizes a high-quality base fluid which ensures increased oxidation stability and outstanding low temperature performance. The combination of this base oil with a top-quality viscosity modifier ensures excellent resistance to breakdown due to excessive shearing and pressure in power-steering systems. The solution also contains additional components which provide detergency, wear protection, rust inhibition, seal protection and anti-foaming characteristics. The formula meets O.E.M. Power Steering fluid performance requirements for Ford, GM, Chrysler, and Nissan.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Clear** |
| Color | N/A | **Dark Red** |
| Odor | N/A | **Bland** |
| Specific Gravity @ 68°F | D4052 | **0.85** |
| Density, U.S. (lbs/gal) @ 68°F | N/A | **7.09** |
| Viscosity, cSt @ 100°C | D445 | **~7.00** |
| Viscosity, cSt @ 40°C | D445 | **~32.0** |
| Viscosity Index | N/A | **180** |
| Boiling Point (°F) | N/A | **≥ 487** |
| Flash Point (°F) (based on components) | N/A | **> 248** |

## 04 // APPLICATION

MOC® Power-Steering Service Solution-Red #0156 should only be used with a MOC® Power-Steering Fluid Exchanger.

1. Follow the MOC® Power-Steering Fluid Exchanger instructions to perform the exchange process.
2. Dispose of used fluid in accordance with local, state, and federal regulations.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **64 oz.** | 4 | 16 lbs. |