**#0417**

# MULTI-VEHICLE SYNTHETIC CVT FLUID




## 01 // OUTSTANDING FEATURES

- Highly resistant to shearing, oxidation and thermal breakdown.
- Provides excellent flow properties at low temperatures and film protection at high temperatures.
- Outstanding anti-wear properties to protect transmission parts.
- Meets the friction and anti-shutter requirements of both belt and chain type CVT.

## 02 // DESCRIPTION

A premium blend of additives to ensure superior component protection and enhanced service reliability. In order to meet the performance needs of a wide variety of CVT systems, this product has been specially designed to provide optimal metal-to-metal friction, anti-shudder durability and shear stability. It protects against wear and is fortified to provide unsurpassed oxidation stability. This product may be used in both chain and belt-type CVT. It is not recommended for use in standard automatic transmissions or as a replacement for ATF. Multi-Vehicle Synthetic CVT Fluid is suitable for use in the following applications: Audi/VW ® (TL 52180; G 052 180/516) Chain | Toyota (TC, FE*) Belt | Ford ® (CVT30 / Mercon ® C) Chain | Hyundai ® / Kia (SP-CVT-1) Belt Subaru ® (Lineartronic K0425, CV-30, HT, e-CVTF, i-CVTF) Chain | Suzuki ® (TC / NS-2 / CVT Green 1 & 2*) Belt | Honda ® (HMMF, HCF-2) Belt | Dodge ® / Jeep ® (NS-2 / CVTF+4) Belt | Nissan ® (NS-1, NS-2, NS-3*) Belt | GM ® /Saturn ® (DEX-CVT) Belt | Mitsubishi ® (CVTF-J1 / J-4*) Belt | Ford ® (CVT23) Belt | Mini Cooper ® (EZL 799A) Belt | Mercedes Benz ® (236.20) Belt

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Clear Oil** |
| Color | N/A | **Amber** |
| Density (g/mL) | D4052 | **0.83** |
| Density, U.S. (lbs/gal), calculated | N/A | **~7.1** |
| Viscosity @ 100° C, cSt | D445 | **~ 7.0** |
| Viscosity, @ 40° C, cSt | D445 | **~ 33.5** |
| Viscosity Index | N/A | **~180** |
| Brookfield Viscosity @ -40° C, cPs | D2983 | **~21,700** |
| Flash Point (°F) (based on components) | N/A | **≥ 266** |

## 04 // APPLICATION

Use in continuously variable transmissions according to equipment manufacturer's recommendations. DO NOT use in standard automatic transmissions or Hybrid CVT units (Toyota® and Ford® .) These units require a specific ATF.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **1 qt.** | 12 | 24 lbs. |
| **1 gal.** | 4 | 32 lbs. |
| **5 qt.** | 3 | 30 lbs. |