#0421

SYNTHETIC HIGH-PERFORMANCE ULV ATF



01 // OUTSTANDING FEATURES

- Highly resistant to shear, oxidation and thermal breakdown.
- Provides excellent flow properties at low temperatures and film protection at high temperatures.
- Outstanding anti-wear properties to protect transmission parts.
- Premium, full synthetic formula.

02 // DESCRIPTION

An advanced lubricant designed to provide superior component protection and enhanced service reliability when used in high performance or 8, 9 & 10 speed transmissions. Synthetic ATF HP is specially formulated for maximum high & low temp stability, oxidation resistance and wear prevention, while maintaining essential frictional and shifting properties. This premium, PAO-based formula meets or exceeds the performance criteria for a wide range of AT fluids and may be used in place of synthetic fluids specified by several vehicle manufacturers, including GM ® Dex HP (19417577, 8L45/90, 10L80/90) GM ® Dex ULV (19352619), Honda ® 2.0, Mopar ® 8 & 9 Speed ATF, Ford Mercon ® ULV ATF, VOLVO ® (31492172), Mazda ® A7 and Nissan Matic P & R (please note the Matic fluids are amber in color)

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Oil**
Color	N/A	**Red**
Density (g/mL)	D4052	**0.84**
Density, U.S. (lbs/gal), calculated	N/A	**6.99**
Viscosity @ 100°C, cSt	D445	**4.1 - 4.8**
Viscosity @ 40°C, cSt	D445	**~20.0l**
Viscosity @ -40°C, cP	D2983	**~6000**
Flash Point, COC°C	D92	**~182**

04 // APPLICATION

Use in automatic transmissions according to equipment manufacturer's recommendations. DO NOT use in transmissions that require CVT or Type F fluids.

05 // PACKAGING

FILL	CASE QTY	CASE WT
1 quart	12 Bottles	24.5 lbs.
1 gal	4 Bottles	31 lbs.