#0601

HEAVY-DUTY DOT 4 BRAKE FLUID



01 // OUTSTANDING FEATURES

- Contains special additives and esters for excellent high-temperature protection and moisture resistance.
- Extremely high-boiling point formula Dry ERBP: > 260°C (> 500°F), Wet ERBP: >175°C (>346°F)
- Exceeds DOT specifications for DOT 4 brake fluid (DOT minimum is 446°F).
- Two convenient sizes for use with fluid exchange equipment.
- Product is compatible and may be used in place of DOT 3.

02 // DESCRIPTION

A high quality product which meets and exceeds the DOT specifications for DOT 4 brake fluid.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear & Bright**
Color	N/A	**Light Yellow**
Odor	N/A	**Mild**
Density, U.S. (g/ml) @ 68°F	D4052	**~1.06**
Density, U.S. (lbs/gal) (Calculated)	N/A	**~8.85**
Viscosity @-40 °C, cSt	SAE J-1704	**~1,090**
Dry ERBP, °F	SAE J-I704	**~500**
Wet ERBP, °F	SAE J-I704	**~350**
Water %	SAE J1704	**<0.3**

04 // APPLICATION

This product is to be used with a #98000 MOC® Pure Brake™ Brake-Fluid Exchanger. Follow directions in the machine's instruction manual for use of this product.

05 // PACKAGING

FILL	CASE QTY	CASE WT
32 oz.	12 Bottles	29.6 lbs.
53 oz.	4 Bottles	16.39 lbs.