#0123

POWER STEERING SERVICE SOLUTION



01 // OUTSTANDING FEATURES

- Reduces friction and heat that can wear out the pump, valves and gears.
- Enhanced resistance to breakdown due to shearing and system pressure.
- Conditions seals and hoses to help prevent cracks and leaks.
- Helps extend system life by reducing wear on internal components.
- Helps reduce squeals and chatter due to foaming.
- Outstanding cold weather performance.

02 // DESCRIPTION

A fortified power-steering fluid blend that is used in conjunction with a MOC® Power-Steering Fluid Exchanger. This product contains a special additive package for enhanced shear stability, anti-wear and thermal stability. It is suitable for use in Ford ®, GM ®, Chrysler ®, and many other types of vehicles. Important: This fluid is NOT suitable for use in Honda ® /Acura ® vehicles.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear**
Color	N/A	**Light Amber**
Odor	N/A	**Bland**
Density (g/mL)	D4052	**0.85**
Density, U.S. (lbs/gal), calculated	N/A	**7.07**
Viscosity,cSt @ 100°C	D445	**~7.4**
Viscosity,cSt @ 40°C	D445	**~36**
Viscosity Index	D2270	**~180**
Boiling Point(°F)	N/A	**>487**
Flash Point(°F)(based on components)	N/A	**>248**

04 // APPLICATION

MOC® Power-Steering Service Solution #01231 should only be used with a MOC® Power-Steering Fluid Exchanger.

1. Follow the MOC® Power-Steering Fluid Exchanger instructions to perform the exchange process.
2. Dispose of used fluid in accordance with local, state and federal regulations.

05 // PACKAGING

FILL	CASE QTY	CASE WT
64 oz.	4	17 lbs.