**#0147**

# GEAR GUARD PLUS SAE 75W-85




## 01 // OUTSTANDING FEATURES

- Superior lubrication and protection for bearings and gears.
- Helps prevent wear, pitting, gear noise and corrosion under high-load conditions.
- Excellent fluidity and protection in extreme temperatures.
- Contains special additives to reduce chattering in limited- slip differentials.
- Meets stringent industry standards, including API GL-5, MT-1, MILL 2105 D-E, 2105E and SAE J2360 specifications.

## 02 // DESCRIPTION

A multigrade synthetic (polyalphaolefin), A.P.I. GL-5 rated gear oil formulated to SAE 75W-85 viscosity. It is a premium extreme-pressure lubricant designed for use in axle applications requiring limited-slip performance but can also be used in conventional differentials. MOC® Gear Guard™ Plus SAE 75W-85 is a versatile product that can be used in place of SAE 75W, SAE 80, SAE 85 oils and eliminates the need for a supplemental friction modifier. It is designed to provide excellent extreme pressure protection, load carrying capacity, anti-foam performance, corrosion protection, and thermal stability protection.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Oil** |
| Color | N/A | **Amber** |
| Odor | N/A | **Petroleum** |
| Density (g/mL) @68 °F | D4052 | **0.85** |
| Density, U.S. (lbs/gal), calculated @68 °F | N/A | **7.09** |
| Viscosity @ 100°C, cSt | D445 | **13.5-18.5** |
| Viscosity @ 40°C, cSt | D445 | **~120** |
| Brookfield Viscosity @ -40° C, cP | D2983 | **<150,000** |

## 04 // APPLICATION

Follow vehicle manufacturer's recommendations for use of product. Gear Guard™ Plus is designed to be used in conjunction with MOC® Differential/Driveline service equipment and tools.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **1 quart** | 12 Bottles | 24.14 lbs. |