**#0414**

# GEAR GUARD SAE 75W-90




## 01 // OUTSTANDING FEATURES

- Superior lubrication and protection for bearings and gears.
- Helps prevent wear, pitting and corrosion under high- load conditions. Helps reduce gear noise and increases driveline efficiency.
- Meets stringent industry standards including A.P.I. GL-5, MT-1 and SAE J2360 specifications.

## 02 // DESCRIPTION

A synthetic Polyalphaolefin, A.P.I. GL-5 rated gear oil formulated to SAE 75W-90 viscosity. It is a versatile extreme-pressure lubricant designed for use in conventional differentials, limited-slip differentials, and manual transmissions. MOC® Gear Guard™ SAE 75W-90 can be used in place of SAE 75W, SAE 75W-85, SAE 80, SAE 80W-90, or SAE 90 in a wide range of domestic and foreign vehicles.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Clear & Bright** |
| Color | N/A | **Yellow** |
| Odor | N/A | **Sulfur** |
| Density (g/mL) | D4052 | **0.84** |
| Density, U.S. (lbs/gal), calculated | N/A | **7.10** |
| Viscosity @ 100°C, cSt | D445 | **~14.0** |
| Viscosity @ 40°C, cSt | D445 | **~60** |
| Flash Point °F (based on components) | N/A | **>230** |
| Brookfield Viscosity @ -40°C, cP | D2983 | **<100,000** |

## 04 // APPLICATION

Follow vehicle manufacturer's recommendations for use of product. Gear Guard™ is designed to be used in conjunction with MOC® Differential / Driveline service and tools. NOTE: Limited-slip differentials require the use of MOC® Limited-Slip Concentrate #0149 with MOC® Gear Guard™.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **1 qt.** | 12 | 24 lbs. |
| **16 gal.** | 2 | 248 lbs. |