#0415

ULTRA SHIFT



01 // OUTSTANDING FEATURES

- Superior lubrication and protection for bearings and gears.
- Helps prevent wear, pitting and corrosion under high-load conditions. Promotes excellent shift quality and synchronizer performance in manual transmissions.
- Compatible with manual transmission components such as bronze, brass, copper, and elastomer material.

02 // DESCRIPTION

A full synthetic gear lubricant specially formulated for a wide range of manual transmissions, transaxles, and transfer cases. The combination of high-quality base oils and a multi-functional additive system in Ultra Shift™ provides superior anti-wear protection, shear stability and low temperature fluidity. This premium formula may be effectively used in all domestic and foreign vehicles where GL-4 gear oil or ATF is specified by the vehicle manufacturer. Ultra Shift™ is recommended in applications where GM ® Part #12345349, GM ® Auto Trak II Part #1237508, Toyota LF 75W 08885-81080, Ford ® Part #D80Z19C547A & ESRY 19C547, Chrysler ® Part #4773167, or Mercedes Benz ® Part #900260315 are specified.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear**
Color	N/A	**Yellow**
Odor	N/A	**Sulfur**
Density (g/mL)	D4052	**0.83**
Density, U.S. (lbs/gal), calculated	N/A	**6.9**
Viscosity @ 100°C, cSt	D445	**~9.7**
Viscosity @ 40°C, cSt	D445	**~49**
Flash Point °F (PMCC)	D93	**>211**
Brookfield Viscosity @ -40°C, cPs	D2983	**21,795**

04 // APPLICATION

Use quantity in accordance with vehicle manufacturer's recommendations.

05 // PACKAGING

FILL	CASE QTY	CASE WT
1 qt.	12	24 lbs.