#0600

HEAVY-DUTY DOT 3 BRAKE FLUID



01 // OUTSTANDING FEATURES

- High-boiling point formula (ERBP of ~485°F).
- Exceeds DOT specifications for DOT 3 brake fluid (DOT minimum is 404°F).
- Two convenient sizes for use with fluid exchange equipment.
- Excellent high-temperature protection and moisture resistance.

02 // DESCRIPTION

A high quality product which meets and exceeds the DOT specifications for DOT 3 brake fluid.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear & Bright**
Color	N/A	**Light Straw**
Odor	N/A	**Mild**
Specific Gravity @ 68°F	D4052	**~1.04**
Density, U.S. (lbs/gal) (Calculated)	N/A	**~8.7**
Viscosity, cSt @ -40°C	SAE J-I703	**~1,000**
Dry ERBP, °F	SAE J-I703	**~490**
Wet ERBP, °F	SAE J-I703	**~305**
% Water	D1209	**<0.3**

04 // APPLICATION

This product is to be used with a #98000 MOC® Pure Brake™ Brake-Fluid Exchanger. Follow directions in the machine's instruction manual for use of this product.

05 // PACKAGING

FILL	CASE QTY	CASE WT
32 oz.	12 Bottles	29.4 lbs.
53 oz.	4 Bottles	15.6 lbs.