**#2160**

# MAGNA GLAZE




## 01 // OUTSTANDING FEATURES

- Seals and brightens all surfaces.
- Low dust formula
- **Versatile** // easy application by hand or high speed and orbital buffers.

**Performance ratings // Abrasiveness 6 // Gloss 5 // Durability 4**

## 02 // DESCRIPTION

A one-step polish for use on all painted surfaces. It removes medium oxidation, cleans, polishes, and protects. Magna Glaze™ is a thick cream with an off-white color (similar to Magna Bright #21403, but more aggressive).

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Viscous cream** |
| Color | N/A | **Off White** |
| Odor | N/A | **Solvent** |
| Density, U.S. (lbs/gal) @ 77°F | D1475 | **~8.60** |
| Solids, % | E1868 | **~18** |
| Brookfield Viscosity,CP | N/A | **30,000** |
| Body Shop Safe | N/A | **Yes** |
| VOC Compliant | N/A | **Yes** |
| Biodegradable | N/A | **No** |

## 04 // APPLICATION

Hand Use: Dampen a clean cloth or applicator and spread Magna Glaze ™ on cloth or vehicle surface. Apply product using even pressure and circular motion. Allow to dry. Use a clean towel to wipe clean. Machine Use: Squirt Magna Bright™ onto vehicle surface. For best results, use an all-wool finish pad. Apply medium to heavy pressure at first, then gradually ease up until polish dries and develops a gloss. For extended protection and additional gloss, apply a finish wax as a final operation. Can be used with all-wool and foam pads.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **1 gal.** | 4 | 34 lbs. |