#0143

COOLING SYSTEM MULTI-TREATMENT



01 // OUTSTANDING FEATURES

- Eliminates the need to use 2 or 3 different products.
- Compatible with all types of coolant
- Proven to increase corrosion inhibiting performance of treated coolant and fortify system services from corrosion damage for an extended period.
- Increases protection of water pump and reduces potential damage to pump surfaces.
- Sealing compounds help stop minor leaks and seal cracks in the radiator and block.

02 // DESCRIPTION

A concentrated additive that provides complete protection for the entire cooling system. It protects the cooling system in four different ways. It contains a concentrated blend of corrosion inhibitors, anti-foaming agents, pump lubricants and sealing compounds. This product contains a unique corrosion and rust inhibitor that enhances protection of iron, aluminum, copper, and solder surfaces. Cooling System Multi-Treatment™ is designed to fortify and extend the service life of antifreeze and is compatible with all types of coolant.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear & Bright**
Color	N/A	**Yellow**
Odor	N/A	**Bland, Mild Ammonia**
pH	D1287	**9-10**
Density (g/mL)	D4052	**1.08**
Density, U.S. (lbs/gal), calculated	D1250	**9.01**
Boiling Point (°F) Based on components	N/A	**>212**
Flash Point (°F) Based on components	N/A	**>232**
VOC %	N/A	**5.00**

04 // APPLICATION

Shake well before using. If used between services, allow cooling system to cool before removing radiator cap to add product.

1. Remove radiator cap and add entire contents of container to cooling system.
2. Replace radiator cap and allow car to idle for 10-15 minutes.

05 // PACKAGING

FILL	CASE QTY	CASE WT
12 oz.	24	22 lbs.