#0148

GEAR GUARD



01 // OUTSTANDING FEATURES

- Superior lubrication and protection for bearings and gears. Helps prevent wear, pitting and corrosion under high-load conditions.
- Excellent fluidity in extreme temperatures.
- Eliminates the need to inventory and use multiple gear oils for different weather conditions.
- Provides proper lubrication in summer and winter.
- Helps reduce gear noise in all conditions due to its multigrade formula and increases driveline efficiency.
- Meets stringent industry standards, including API GL-5, MT-1 and SAE J2360 specifications.

02 // DESCRIPTION

A multi-grade synthetic (polyalphaolefin), A.P.I. GL-5 rated, hypoid gear oil formulated to SAE 75W-140 viscosity. It is a premium extreme-pressure lubricant designed for use in conventional differentials, limited-slip differentials, and manual transmissions. MOC® Gear Guard™ is a versatile product that can be used in place of SAE 75W, Motorcraft SAE 75W-85, SAE 80W-90, SAE 90, or SAE 80W-140 and SAE 85W-140 or SAE 140 oils.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear & Bright**
Color	N/A	**Amber**
Odor	N/A	**Petroleum**
Density (g/mL)	D4052	**~0.86**
Density, U.S. (lbs/gal), calculated	N/A	**~7.18**
Viscosity @ 100°C, cSt	D445	**~26**
Viscosity @ 40°C, cSt	D445	**~212**
Viscosity Index	D2270	**~135.000**

04 // APPLICATION

Follow vehicle manufacturer's recommendations for use of product. Gear Guard™ is designed to be used in conjunction with MOC® Differential/Driveline service and tools. NOTE: Limited-slip differentials require the use of MOC® Limited-Slip Concentrate #0149 with MOC® Gear Guard™.

05 // PACKAGING

FILL	CASE QTY	CASE WT
1 qt..	12	24 lbs.
16 gal.	1 Drum	248 lbs.