#0414

GEAR GUARD SAE 75W-90



01 // OUTSTANDING FEATURES

- Superior lubrication and protection for bearings and gears.
- Helps prevent wear, pitting and corrosion under high- load conditions. Helps reduce gear noise and increases driveline efficiency.
- Meets stringent industry standards including A.P.I. GL-5, MT-1 and SAE J2360 specifications.

02 // DESCRIPTION

A synthetic Polyalphaolefin, A.P.I. GL-5 rated gear oil formulated to SAE 75W-90 viscosity. It is a versatile extreme-pressure lubricant designed for use in conventional differentials, limited-slip differentials, and manual transmissions. MOC® Gear Guard™ SAE 75W-90 can be used in place of SAE 75W, SAE 75W-85, SAE 80, SAE 80W-90, or SAE 90 in a wide range of domestic and foreign vehicles.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear & Bright**
Color	N/A	**Yellow**
Odor	N/A	**Sulfur**
Density (g/mL)	D4052	**0.84**
Density, U.S. (lbs/gal), calculated	N/A	**7.10**
Viscosity @ 100°C, cSt	D445	**~14.0**
Viscosity @ 40°C, cSt	D445	**~60**
Flash Point °F (based on components)	N/A	**>230**
Brookfield Viscosity @ -40°C, cP	D2983	**<100,000**

04 // APPLICATION

Follow vehicle manufacturer's recommendations for use of product. Gear Guard™ is designed to be used in conjunction with MOC® Differential / Driveline service and tools. NOTE: Limited-slip differentials require the use of MOC® Limited-Slip Concentrate #0149 with MOC® Gear Guard™.

05 // PACKAGING

FILL	CASE QTY	CASE WT
1 qt.	12	24 lbs.
16 gal.	2	248 lbs.