#0416

MULTI-VEHICLE SYNTHETIC ATF-CLEAR



01 // OUTSTANDING FEATURES

- Highly resistant to shearing, oxidation and thermal breakdown.
- Provides excellent flow properties at low temperatures and film protection at high temperatures.
- Outstanding anti-wear properties to protect transmission parts.
- Conditions seals and helps prevent leaks.

02 // DESCRIPTION

A special blend of full synthetic base oils combined with a multi-functional additive system that provides superior anti- wear protection and performance in virtually all types of passenger and commercial automatic transmissions. It offers excellent high & low temperature fluidity, shear stability, seal protection and oxidation resistance. This premium formula may be used in place of synthetic fluids required or specified by a wide range of OEMs, including those used for extended drain and severe duty intervals. This product is designed to be used in conjunction with the MOC® ATF Fluid Exchanger #94500 and ATF Cleaner/Supplement Kit #01941. Multi-Vehicle Synthetic ATF-Clear is suitable for use in the following applications: • Audi/VW G-052-990-A2, G-052-162-A1, G055005 A1 • BMW 83220142516, 83229407807 • Ford XT-6-QSP • Jaguar JLM20238 • Mercedes Benz Sheet 236.11 • Peugeot Z000169756 • Porsche 99991754700 • Rolls Royce PL 31493PA • Shell M1375.4 • Voith DIWA, DIAWA.2, .3, .3E, .5 • ZF TE-ML-11B, 5671 090 170, 5671 090 255

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear**
Color	N/A	**Amber**
Density (g/mL)	D4052	**0.83**
Density, U.S. (lbs/gal), calculated	N/A	**6.93**
Viscosity @ 100°C, cSt	D445	**~6**
Viscosity @ 40°C, cSt	D445	**~32**
Viscosity Index, calculated	N/A	**~150**
Brookfield Viscosity @ -40°C, cPs	D97	**<10,000**

04 // APPLICATION

Use in automatic transmissions according to equipment manufacturer's recommendations. DO NOT use in transmissions that require CVT or Type F fluids.

05 // PACKAGING

FILL	CASE QTY	CASE WT
1 gal.	4	31 lbs.
55 gal.	1 Drum	403 lbs.