**#0420**

# MULTI-VEHICLE SYNTHETIC ATF - BLUE




## 01 // OUTSTANDING FEATURES

- Highly resistant to shearing, oxidation and thermal breakdown.
- Provides excellent flow properties at low temperatures and film protection at high temperatures.
- Outstanding anti-wear properties to protect transmission parts.
- Conditions seals and helps prevent leaks.

## 02 // DESCRIPTION

A special blend of fully-synthetic base oils combined with a multi-functional additive system that provides superior anti-wear protection and performance in virtually all types of passenger and commercial automatic transmissions that require newer "low-viscosity" fluid. It offers excellent high & low temperature fluidity, shear stability, seal protection and oxidation resistance. This premium formula may be used in place of synthetic fluids required or specified by a wide range of OEMs, including those used for extended drain and severe duty intervals. This product is designed to be used in conjunction with the MOC® ATF Fluid Exchanger #94500 and ATF Cleaner/Supplement Kit #01941. Multi-Vehicle Synthetic ATF-Blue is suitable for use in all applications where Blue ATF fluid is required. Compatible with Mazda FZ transmissions.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Clear Oil** |
| Color | N/A | **Blue** |
| Density (g/mL) @68 °F | D4052 | **0.83** |
| Density, U.S. (lbs/gal), calculated @68 °F | N/A | **6.93** |
| Viscosity @ 100°C, cSt | D445 | **~6** |
| Viscosity @ 40°C, cSt | D445 | **~32** |
| Viscosity Index, calculated | N/A | **~150** |
| Brookfield Viscosity @ -40°C, cPs | D97 | **<10,000** |

## 04 // APPLICATION

Use in automatic transmissions according to equipment manufacturer's recommendations. DO NOT use in transmissions that require CVT or Type F fluids.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **1 gal** | 4 Bottles | 31 lbs. |
| **3 gal** | 2 Bottles | 46 lbs. |