**#0133**

# A/C QUIET




## 01 // OUTSTANDING FEATURES

- Compatible with R-12 and R-134a refrigerant.
- Compatible with mineral ester, paraffin, and PAG oils.
- Compatible with air-conditioning system components.
- Helps prevent rust and corrosion by neutralizing acids and encapsulating moisture.
- Helps reduce wear and noise in the A/C compressor.

## 02 // DESCRIPTION

A highly effective ester-based oil lubricant for automotive air-conditioning systems. This lubricant performs four key functions: 1. It lubricates the entire air-conditioner system, including the compressor. 2. It helps prevent acid from forming and inhibits corrosion. 3. It encapsulates moisture and keeps it from damaging internal parts. 4. It contains a special color dye for leak detection (under black light). Note: A/C Quiet™ should be added to a system after an A/C service, to quiet a noisy compressor, if refrigerant/oil level is low, as a preventative maintenance step and to detect system leaks.

## 03 // APPLICATION

A/C Quiet™ (#0133 and #0134): Add appropriate amount of A/C Quiet™ to an air-conditioner system using MOC® A/C Quiet™ Injector Tool #76004. Follow A/C system manufacturer's instructions for charging of the system. Note: #01331 (2 oz.) is typically added if the refrigerant/oil level is low if the compressor is noisy and as a preventative maintenance step. Note: #01341 (8 oz.) Is typically added when installing a new A/C unit, retrofitting from R12 to R134a after using MOC® A/C Flush #01321, and to detect system leaks.

## 04 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Clear & Bright** |
| Color | N/A | **Fluorescent Yellow** |
| Odor | N/A | **Mild** |
| Density (g/mL) | D4052 | **0.96** |
| Density, U.S. (lbs/gal), calculated | D1250 | **8.04** |
| Flash Point (°F) PMCC | D92 | **355** |

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **01331 2 oz.** | 24 | 4 lbs. |
| **01334 8 oz.** | 24 | 13 lbs. |