#0604

POWER STEERING FLUSH SOLUTION



01 // OUTSTANDING FEATURES

- Reduces friction and heat that can wear out the pump, valves, and gears.
- Enhanced resistance to breakdown due to shearing and system pressure.
- Conditions seals and hoses to help prevent cracks and leaks.
- Extends system life by reducing wear on internal components.

02 // DESCRIPTION

Designed to remove harmful system deposits and impurities. Use it prior to one of the MOC® Power-Steering Service Solutions to help remove depleted fluid and contaminants. Use only in conjunction with a MOC® Power-Steering Fluid Exchanger.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear**
Color	N/A	**Amber**
Odor	N/A	**Mild Petroleum**
Specific Gravity @ 68°F	D1298	**0.85**
Density, U.S. (lbs/gal) @ 68°F	D1250	**7.1**
Viscosity cSt @ 100°C	D445	**~7**
Viscosity cSt @ 40°C	D445	**~35**
Viscosity Index	D2270	**~200**
Brookfield Viscosity cP @ -40°C	D2983	**~13,000**
Boiling Point (°F)	N/A	**≥ 599**
Flash Point (°F) (based on components)	N/A	**≥ 248**

04 // APPLICATION

Follow the MOC® Power-Steering Fluid Exchanger instructions to perform the exchange process. Dispose of used fluid in accordance with local, state and federal regulations. MOC® Power-Steering Flush Solution #0604 should only be used with a MOC® Power-Steering Fluid Exchanger.

05 // PACKAGING

FILL	CASE QTY	CASE WT
64 oz	4 Bottles	17 lbs.