#16502

OPTIMIZER LIQUID



01 // OUTSTANDING FEATURES

- Loosens and removes stubborn carbon.
- Will not harm catalytic converter or oxygen sensor when used as directed.
- Restores engine performance.
- Designed for “hard-to-fix” problem areas.

02 // DESCRIPTION

A unique liquid cleaner designed to remove carbon and other deposits in the fuel induction system. The blend of solvents and cleaners is specifically designed to address “hard-to-fix” problem areas. Removing carbon from intake valves and combustion chambers can help eliminate cold-starts, hesitation and other drivability problems. The product contains no alcohol and will not harm seals, oxygen sensors or catalytic converters. When used as directed Optimizer™ (Non Aerosol) can be used on all gasoline or diesel engines. It is highly effective as a solution for carbon buildup problems on direct-injected engines.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Aqueous Emulsion**
Color	N/A	**Cloudy Amber**
Odor	N/A	**Solvent**
pH	N/A	**9.5 +/- 0.5**
Specific Gravity @ 68°F (liquid portion)	D1298	**0.96**
Density, U.S. (lbs/gal) @ 68°F	D1250	**8.01**
Flash point °F, PMCC	D 93	**150**
% VOC	N/A	**50**

04 // APPLICATION

Vehicle should be at operating temperature. Recommended Method: Follow instructions for use with #73400 EDR-3 Fuel Machine. Alternate Method:

1. Attach #74100 A.I.S. Tool to Air-Intake System at throttle body opening.
2. Pour Optimizer into canister of #72480 Deluxe Cleaner Application Tool II.
3. Attach outlet hose of Cleaner Application Tool to A.I.S. Tool.
4. Follow instructions for use with #72480 Deluxe Cleaner Application Tool II.

05 // PACKAGING

FILL	CASE QTY	CASE WT
16 oz	12 Cans	14.372 lbs.