**#0101**

# MOTOR OIL CONDITIONER




## 01 // OUTSTANDING FEATURES

- **Improves Performance** // specially formulated to reduce friction and wear.
- **Effective** // protects new engines during break-in and start-up.
- **Reduces Friction** // increases lubricating power of oil.
- **Helps Keep Engines Clean** // contains dispersants and detergents to help prevent sludge deposits.
- **Versatile** // can be used in all types of internal-combustion engines.
- **Compatibility** // designed for use in conventional and synthetic oils.
- Contains no solvents or chlorinated materials.

## 02 // DESCRIPTION

Scientifically formulated to increase performance by reducing friction and wear. MOC® Motor Oil Conditioner contains dispersants and detergents to help prevent sludge buildup. The product is carried by motor oil to where it lubricates internal parts to create a low-friction surface. This reduction in friction can protect new engines during break-in and start-ups. It may be used in all internal-combustion engines, including rotary and diesel.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Oil** |
| Color | N/A | **Brown** |
| Odor | N/A | **Petroleum** |
| Specific Gravity | D1298 | **0.88** |
| Density, U.S. (lbs/gal) @ 68°F, calculated | N/A | **7.32** |
| Viscosity, cSt @ 100°C | D445 | **~4** |
| Boiling Point (°F) | D1120 | **>400** |
| Flash Point (°F), based on components | D93 | **>248** |

## 04 // APPLICATION

Pour entire contents into crankcase with each oil change.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **11 fl. oz. (325 mL)** | 24 | 21 lbs. |