**#0111**

# COOLING-SYSTEM TREATMENT




## 01 // OUTSTANDING FEATURES

- Compatible with all types of coolant (conventional - green, extended life - Dex-Cool, Hybrid - GO-5, Asian and European formulas). Based on ASTM D4334 test results.
- Proven to increase corrosion inhibiting performance of treated coolant and fortify system surfaces from corrosion damage for an extended period. Based on ASTM D3306 test results.
- Increases protection of water pump and reduces potential damage to pump surfaces. Based on ASTM D2809 test results.

## 02 // DESCRIPTION

A universal formula that is compatible with all types of coolant-antifreeze. This product contains a unique corrosion and rust inhibitor technology that enhances protection of cooling system metals such as iron, aluminum, copper, and solder. It contains anti-foaming agents and provides additional protection to water pumps.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Clear & Bright** |
| Color | N/A | **Yellow -Brown** |
| Odor | N/A | **Faint Ammonia** |
| pH | D1287 | **8.7-9.5** |
| Density (g/ml) | D4052 | **1.06** |
| Density, U.S. (lbs/gal) calculated | N/A | **8.85** |
| Boiling Point(°F) | N/A | **>212** |
| Flash Point(°F) based on components | N/A | **>232** |

## 04 // APPLICATION

Add one bottle of MOC® Cooling System Treatment to the cooling system any time a service is performed, or additional rust and corrosion protection is desired.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **8 oz.** | 24 | 16 lbs. |