#0122

PREMIUM DIESEL ENGINE TREATMENT



01 // OUTSTANDING FEATURES

- Significantly reduces friction and improves load bearing ability by 180% (based on ASTM Test D3233A).
- Reduces sludge and varnish.
- Greatly improves engine oil's ability to resist oxidation breakdown. (Based on ASTM D4742 TFOUT tests.)
- Protects vital engine parts during start-ups and new car break-in periods.
- Compatible with all diesel oils including synthetic and multi- grade.

02 // DESCRIPTION

Designed to fortify oil in modern high-output diesel engines that is subject to extreme pressure and temperatures. Increased soot and sulfur accumulation is common in today's diesel engine oil. These contaminants combine with moisture to form acids that can quickly cause corrosive wear and damage to engine components. This full-synthetic formula contains advanced antioxidants, dispersants and lubricants that provide long-lasting protection and maintain oil performance. Premium Diesel Engine Treatment neutralizes acids, prevents sludge, reduces friction, stabilizes viscosity, and helps disperse soot buildup. Pour entire contents (11 oz.) into crankcase with each oil change.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear & Bright**
Color	N/A	**Brown**
Odor	N/A	**Hydrocarbon**
Density (g/ml)	D4052	**0.88**
Density, U.S. (lbs/gal) calculated	N/A	**7.34**
Viscosity,cSt @ 100°C	D445	**~9**
Flash Point (°F) PMCC	N/A	**≥248**
Boiling Point (°F)	N/A	**≥455**

04 // APPLICATION

Pour entire contents of bottle into crankcase after or between an oil change.

05 // PACKAGING

FILL	CASE QTY	CASE WT
11 oz.	24	21 lbs.