#0149

LIMITED-SLIP CONCENTRATE

01 // OUTSTANDING FEATURES

- Enhances limited-slip performance (anti-chatter) of rear axles.
- Compatible with most conventional and synthetic gear oils.
- Eliminates the need for inventory multiple gear oils.

02 // DESCRIPTION

Designed to prevent chatter in limited-slip differentials and full-time four-wheel drive transfer cases. This product helps quiet gears in the differential and fortify standard gear lubricants. It is designed to be used with any GL-5 gear lubricant in Limited-slip applications. Recommended for rear-wheel drive passenger cars, trucks, and sport utility vehicles.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear & Bright**
Color	N/A	**Amber**
Odor	N/A	**Petroleum**
Density (g/mL)	D4052	**0.91**
Density, U.S. (lbs/gal), calculated	N/A	**7.60**
Viscosity, cSt @ 100°C	D445	**~7**
Viscosity, cSt @ 40°C	D445	**~46**
Flash Point(°F), PMCC	D93	**≥257**

04 // APPLICATION

Add 1-part concentrate to every 25 parts of gear lubricant. Add treated gear lubricant to vehicle. Do not overfill system. For best results, use MOC® Limited-Slip Concentrate with MOC® Gear Guard™ #0148 or #0414 gear oil. Product may be added between services or as needed.

05 // PACKAGING

FILL	CASE QTY	CASE WT
4 oz.	12	4 lbs.