#0447

SYNTHETIC HIGH-PERFORMANCE ULV ATF CLEAR



01 // OUTSTANDING FEATURES

- Highly resistant to shear, oxidation and thermal breakdown.
- Provides excellent flow properties at low temperatures and film protection at high temperatures.
- Outstanding anti-wear properties to protect transmission parts.
- Premium, full synthetic formula.

02 // DESCRIPTION

An advanced lubricant designed to provide superior component protection and enhanced service reliability when used in high performance or 8, 9 & 10 speed transmissions. Synthetic ATF HP is specially formulated for maximum high & low temp stability, oxidation resistance and wear prevention, while maintaining essential frictional and shifting properties. This premium, full synthetic formula meets or exceeds the performance criteria for a wide range of AT fluids and may be used in place of synthetic fluids specified by several vehicle manufacturers, including GM ® Dex HP (8L45 / 90, 10L80 / 90), GM ® Dex ULV (19352619), Honda ® 2.0, Mopar ® 8 & 9 Speed ATF, Mercon ® ULV ATF, Nissan ® Matic P & R & Mazda ® A7 ATF.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Oil**
Color	N/A	**Amber**
Density (g/mL)	D4052	**0.82 - 0.85**
Density, U.S. (lbs/gal), calculated	N/A	**6.84 - 7.10**
Viscosity @ 100°C, cSt	D445	**4.1 - 4.50**
Viscosity @ 40°C, cSt	D445	**13.5 - 19**
Viscosity Index	D2983	**158 - 234**

04 // APPLICATION

Use in automatic transmissions according to equipment manufacturer's recommendations. DO NOT use in transmissions that require CVT or Type F fluids.

05 // PACKAGING

FILL	CASE QTY	CASE WT
1 quart	12 Bottles	24.5 lbs.