#0618

TECH GRADE POWER STEERING FLUID

01 // OUTSTANDING FEATURES

- Reduces friction and heat that can wear out the pump, valves, and gears.
- Highly resistant to breakdown due to shearing and system pressure (based on Sonic Shear test).
- Conditions seals and hoses to help prevent cracks and leaks.
- Helps extend system life by reducing wear on internal components.
- Helps reduce squeals and chatter due to foaming.
- Outstanding cold weather performance. Avoids high viscosity at -40°C.

02 // DESCRIPTION

A fortified power-steering fluid blend that utilizes a high-quality base fluid which ensures increased oxidation stability and outstanding low temperature performance. The combination of this base oil with a top-quality viscosity modifier ensures excellent resistance to breakdown due to excessive shearing and pressure in power-steering systems. The solution also contains additional components which provide detergency, wear protection, rust inhibition, seal protection and anti-foaming characteristics. The formula is suitable for use in place of O.E.M. power-steering fluids in Honda ® /Acura ®, Ford ®, GM ®, Chrysler ® and most vehicles. NOTE: Can be packaged and sold in combination with MOC® Power-Steering Fluid Conditioner #0115.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear**
Color	N/A	**Amber**
Odor	N/A	**Mild Petroleum**
Density, U.S. (g/ml) @ 68°F	D4052	**0.85**
Density, U.S. (lbs/gal) @ 68°F (calculated)	N/A	**7.1**
Viscosity cSt @ 100°C	D445	**~7**
Viscosity cSt @ 40°C	D445	**~35**
Viscosity Index	D2270	**~200**
Brookfield Viscosity cP @ -40°C	D2983	**~13,000**
Boiling Point (°F) (based on components)	N/A	**≥ 599**
Flash Point (°F) (based on components)	N/A	**≥ 248**

04 // APPLICATION

Follow the MOC® Power-Steering Fluid Exchanger instructions to perform the exchange process. Dispose of used fluid in accordance with local, state and federal regulations. MOC® Tech Grade Power-Steering Service Fluid #0618 should only be used with a MOC® Power-Steering Fluid Exchanger.

05 // PACKAGING

FILL	CASE QTY	CASE WT
64 oz	4 Bottles	17 lbs.