#0109

COOLING-SYSTEM FAST FLUSH



01 // OUTSTANDING FEATURES

- Non-acid.
- Requires no neutralizer.
- Highly effective at removing scale and sediment from system surfaces.
- Can be used on radiator plastic and aluminum components.

02 // DESCRIPTION

A powerful, convenient, one-step radiator and cooling-system cleaner. It is formulated to quickly breakdown and suspend rust, scale, and sediment. This non-acid-base product needs no neutralizer and is compatible with plastic and aluminum.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear & Bright**
Color	N/A	**Colorless to pale yellow**
Odor	N/A	**Mild**
pH	N/A	**7-7.5**
Density (g/mL)	D4052	**1.06**
'Density, U.S. (lbs/gal), calculated	N/A	**8.87**
Boiling Point(°F)	N/A	**>212**

04 // APPLICATION

Allow system to cool before removing radiator cap.

1. Remove radiator cap.
2. Pour Fast Flush into radiator.
3. Replace radiator cap.
4. Run engine at operating temperature for ten to fifteen minutes.
5. Flush system with a MOC® Coolant Exchanger Machine. Refer to the machine's instructions for additional details and information.

05 // PACKAGING

FILL	CASE QTY	CASE WT
8 oz.	24	16 lbs.