**#0421**

# SYNTHETIC HIGH-PERFORMANCE ULV ATF




## 01 // OUTSTANDING FEATURES

- Highly resistant to shear, oxidation and thermal breakdown.
- Provides excellent flow properties at low temperatures and film protection at high temperatures.
- Outstanding anti-wear properties to protect transmission parts.
- Premium, full synthetic formula.

## 02 // DESCRIPTION

An advanced lubricant designed to provide superior component protection and enhanced service reliability when used in high performance or 8, 9 & 10 speed transmissions. Synthetic ATF HP is specially formulated for maximum high & low temp stability, oxidation resistance and wear prevention, while maintaining essential frictional and shifting properties. This premium, PAO-based formula meets or exceeds the performance criteria for a wide range of AT fluids and may be used in place of synthetic fluids specified by several vehicle manufacturers, including GM ® Dex HP (19417577, 8L45/90, 10L80/90) GM ® Dex ULV (19352619), Honda ® 2.0, Mopar ® 8 & 9 Speed ATF, Ford Mercon ® ULV ATF, VOLVO ® (31492172), Mazda ® A7 and Nissan Matic P & R (please note the Matic fluids are amber in color)

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Oil** |
| Color | N/A | **Red** |
| Density (g/mL) | D4052 | **0.84** |
| Density, U.S. (lbs/gal), calculated | N/A | **6.99** |
| Viscosity @ 100°C, cSt | D445 | **4.1 - 4.8** |
| Viscosity @ 40°C, cSt | D445 | **~20.0l** |
| Viscosity @ -40°C, cP | D2983 | **~6000** |
| Flash Point, COC°C | D92 | **~182** |

## 04 // APPLICATION

Use in automatic transmissions according to equipment manufacturer's recommendations. DO NOT use in transmissions that require CVT or Type F fluids.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **1 quart** | 12 Bottles | 24.5 lbs. |
| **1 gal** | 4 Bottles | 31 lbs. |