**#1090**

# DISSOLVE IT




## 01 // OUTSTANDING FEATURES

- Removes built-up contaminants and debris quickly and easily.
- Can avoid the need for disassembly of parts.
- Just spray and allow surface to dry.
- Contains no fluorocarbons or chlorinated solvents.
- Not for sale or use in California and OTC States.

## 02 // DESCRIPTION

A specially formulated blend of solvents designed to dissolve, disperse and remove contaminants and other organic material from a variety of surfaces. This non-chlorinated, CFC-free formula dries quickly and does not leave a residue or oily film behind. The multi-purpose solvent works well on metal parts, equipment and for various automotive or industrial uses.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Organic Solvents - Compressed Gas** |
| Color (liquid portion) | N/A | **Colorless to Yellow** |
| Odor | N/A | **Sweet** |
| Density, U.S. (lbs/gal) @ 68°F (liquid portion) | D4052 | **5.92** |
| Aerosol Flammability, NFPA Rating | N/A | **Level 3 Aerosol** |
| Can Pressure, psi | N/A | **~ 100** |
| % V.O.C | N/A | **95** |

## 04 // APPLICATION

First test product on an inconspicuous area to determine color fastness and compatibility before using on entire surface.

1. Hold can 8 to 12 inches from surface to be cleaned.
2. Spray liberally until surface is clean.
3. Allow to air dry or remove excess with an absorbent towel or cloth. Note: For harder-to-remove contaminants, spray a clean cloth with product and wipe surface.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **13 oz.** | 12 cans | 13.1 lbs. |