#0417

MULTI-VEHICLE SYNTHETIC CVT FLUID



01 // OUTSTANDING FEATURES

- Highly resistant to shearing, oxidation and thermal breakdown.
- Provides excellent flow properties at low temperatures and film protection at high temperatures.
- Outstanding anti-wear properties to protect transmission parts.
- Meets the friction and anti-shutter requirements of both belt and chain type CVT.

02 // DESCRIPTION

A premium blend of additives to ensure superior component protection and enhanced service reliability. In order to meet the performance needs of a wide variety of CVT systems, this product has been specially designed to provide optimal metal-to-metal friction, anti-shudder durability and shear stability. It protects against wear and is fortified to provide unsurpassed oxidation stability. This product may be used in both chain and belt-type CVT. It is not recommended for use in standard automatic transmissions or as a replacement for ATF. Multi-Vehicle Synthetic CVT Fluid is suitable for use in the following applications: Audi/VW ® (TL 52180; G 052 180/516) Chain | Toyota (TC, FE*) Belt | Ford ® (CVT30 / Mercon ® C) Chain | Hyundai ® / Kia (SP-CVT-1) Belt Subaru ® (Lineartronic K0425, CV-30, HT, e-CVTF, i-CVTF) Chain | Suzuki ® (TC / NS-2 / CVT Green 1 & 2*) Belt | Honda ® (HMMF, HCF-2) Belt | Dodge ® / Jeep ® (NS-2 / CVTF+4) Belt | Nissan ® (NS-1, NS-2, NS-3*) Belt | GM ® /Saturn ® (DEX-CVT) Belt | Mitsubishi ® (CVTF-J1 / J-4*) Belt | Ford ® (CVT23) Belt | Mini Cooper ® (EZL 799A) Belt | Mercedes Benz ® (236.20) Belt

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear Oil**
Color	N/A	**Amber**
Density (g/mL)	D4052	**0.83**
Density, U.S. (lbs/gal), calculated	N/A	**~7.1**
Viscosity @ 100° C, cSt	D445	**~ 7.0**
Viscosity, @ 40° C, cSt	D445	**~ 33.5**
Viscosity Index	N/A	**~180**
Brookfield Viscosity @ -40° C, cPs	D2983	**~21,700**
Flash Point (°F) (based on components)	N/A	**≥ 266**

04 // APPLICATION

Use in continuously variable transmissions according to equipment manufacturer's recommendations. DO NOT use in standard automatic transmissions or Hybrid CVT units (Toyota® and Ford® .) These units require a specific ATF.

05 // PACKAGING

FILL	CASE QTY	CASE WT
1 qt.	12	24 lbs.
1 gal.	4	32 lbs.
5 qt.	3	30 lbs.