#0420

MULTI-VEHICLE SYNTHETIC ATF - BLUE



01 // OUTSTANDING FEATURES

- Highly resistant to shearing, oxidation and thermal breakdown.
- Provides excellent flow properties at low temperatures and film protection at high temperatures.
- Outstanding anti-wear properties to protect transmission parts.
- Conditions seals and helps prevent leaks.

02 // DESCRIPTION

A special blend of fully-synthetic base oils combined with a multi-functional additive system that provides superior anti-wear protection and performance in virtually all types of passenger and commercial automatic transmissions that require newer "low-viscosity" fluid. It offers excellent high & low temperature fluidity, shear stability, seal protection and oxidation resistance. This premium formula may be used in place of synthetic fluids required or specified by a wide range of OEMs, including those used for extended drain and severe duty intervals. This product is designed to be used in conjunction with the MOC® ATF Fluid Exchanger #94500 and ATF Cleaner/Supplement Kit #01941. Multi-Vehicle Synthetic ATF-Blue is suitable for use in all applications where Blue ATF fluid is required. Compatible with Mazda FZ transmissions.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear Oil**
Color	N/A	**Blue**
Density (g/mL) @68 °F	D4052	**0.83**
Density, U.S. (lbs/gal), calculated @68 °F	N/A	**6.93**
Viscosity @ 100°C, cSt	D445	**~6**
Viscosity @ 40°C, cSt	D445	**~32**
Viscosity Index, calculated	N/A	**~150**
Brookfield Viscosity @ -40°C, cPs	D97	**<10,000**

04 // APPLICATION

Use in automatic transmissions according to equipment manufacturer's recommendations. DO NOT use in transmissions that require CVT or Type F fluids.

05 // PACKAGING

FILL	CASE QTY	CASE WT
1 gal	4 Bottles	31 lbs.
3 gal	2 Bottles	46 lbs.