#0603

ULTRA DOT 4-LV BRAKE FLUID



01 // OUTSTANDING FEATURES

- Low viscosity formulation, faster response at lower temperatures.
- High-boiling point formula (ERBP of ~265 °C / 509 °F).
- Wet boiling point (ERBP of ~170 °C / 338°F).
- Ideal for use in vehicles with ESC and ABS brake systems
- Resists moisture absorption and retention.
- Do not mix with DOT 5 Silicone-Based brake fluid

02 // DESCRIPTION

A premium, low viscosity brake fluid recommended for use in vehicles fitted with ESC (Electronic Stability Control), ABS (Anti-lock Braking System) and ASR (Acceleration Slip Regulation). Ultra DOT 4 LV is fully tested and certified to meet or exceed technical standards including: FMVSS 116, SAE J1704 and ISO 4925 Class 6. IMPORTANT: Do not mix with DOT 5 Silicone-Based Brake Fluid

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear & Bright**
Color	N/A	**Pale Yellow**
Odor	N/A	**Mild**
Specific Gravity @ 68°F	D4052	**~1.05**
Density, U.S. (lbs/gal) (Calculated)	N/A	**~8.76**
Kinematic Viscosity, cSt@ -40°C	FMVSS 116	**~549**
Kinematic Viscosity, cSt@ 100°C	FMVSS 116	**~1.9**
Dry ERBP,°F	FMVSS 116	**~504**
Wet ERBP,°F	FMVSS 116	**~336**

04 // APPLICATION

This product is to be used with a #98000 MOC® Pure Brake™ Brake-Fluid Exchanger. Follow directions in the machine's instruction manual for use of this product.

05 // PACKAGING

FILL	CASE QTY	CASE WT
32 oz.	12 Bottles	29.6 lbs.
53 oz.	4 Bottles	25.2 lbs.