**#0657**

# ADVANCED ENGINE TREATMENT




## 01 // OUTSTANDING FEATURES

- Significantly reduces friction and improves load bearing ability by 80%(based on ASTM Test D3233A).
- Reduces sludge and varnish. Detergents and dispersants chemically combine with solid-combustion debris, preventing this debris from creating deposits on engine parts.
- Greatly improves engine oil's ability to resist oxidation breakdown. (Based on ASTM D4742 TFOUT tests)
- Protects vital engine parts between extended oil changes up to 10,000 miles.
- Compatible with gas, diesel, turbo and supercharged engines. Both synthetic and regular oil.

## 02 // DESCRIPTION

Advanced Engine Treatment #0657 is designed to fortify motor oil and protect lubricated parts of the engine between extended oil-change intervals common on modern vehicles. This full-synthetic formula contains advanced antioxidants, dispersants and lubricants that provide long-lasting protection and maintain oil performance. MOC® Advanced Engine Treatment neutralizes acids, prevents sludge, reduces friction, stabilizes viscosity, and helps disperse soot buildup.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Oil** |
| Color | N/A | **Amber** |
| Odor | N/A | **Petroleum** |
| Density (g/mL) @68 °F | D4250 | **0.84** |
| Density, U.S. (lbs/gal), calculated @68 °F | N/A | **7.01** |
| Viscosity,cSt @ 100°C | D445 | **7.2** |
| Flash Point (°F) Based on components | N/A | **≥302** |
| Boiling Point (°F) Based on components | N/A | **≥777** |

## 04 // APPLICATION

Pour entire contents (12 oz.) into crankcase after or between an oil change.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **12 oz.** | 24 | 19.14 lbs. |