#0111

COOLING-SYSTEM TREATMENT



01 // OUTSTANDING FEATURES

- Compatible with all types of coolant (conventional - green, extended life - Dex-Cool, Hybrid - GO-5, Asian and European formulas). Based on ASTM D4334 test results.
- Proven to increase corrosion inhibiting performance of treated coolant and fortify system surfaces from corrosion damage for an extended period. Based on ASTM D3306 test results.
- Increases protection of water pump and reduces potential damage to pump surfaces. Based on ASTM D2809 test results.

02 // DESCRIPTION

A universal formula that is compatible with all types of coolant-antifreeze. This product contains a unique corrosion and rust inhibitor technology that enhances protection of cooling system metals such as iron, aluminum, copper, and solder. It contains anti-foaming agents and provides additional protection to water pumps.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear & Bright**
Color	N/A	**Yellow -Brown**
Odor	N/A	**Faint Ammonia**
pH	D1287	**8.7-9.5**
Density (g/ml)	D4052	**1.06**
Density, U.S. (lbs/gal) calculated	N/A	**8.85**
Boiling Point(°F)	N/A	**>212**
Flash Point(°F) based on components	N/A	**>232**

04 // APPLICATION

Add one bottle of MOC® Cooling System Treatment to the cooling system any time a service is performed, or additional rust and corrosion protection is desired.

05 // PACKAGING

FILL	CASE QTY	CASE WT
8 oz.	24	16 lbs.