**#0415**

# ULTRA SHIFT




## 01 // OUTSTANDING FEATURES

- Superior lubrication and protection for bearings and gears.
- Helps prevent wear, pitting and corrosion under high-load conditions. Promotes excellent shift quality and synchronizer performance in manual transmissions.
- Compatible with manual transmission components such as bronze, brass, copper, and elastomer material.

## 02 // DESCRIPTION

A full synthetic gear lubricant specially formulated for a wide range of manual transmissions, transaxles, and transfer cases. The combination of high-quality base oils and a multi-functional additive system in Ultra Shift™ provides superior anti-wear protection, shear stability and low temperature fluidity. This premium formula may be effectively used in all domestic and foreign vehicles where GL-4 gear oil or ATF is specified by the vehicle manufacturer. Ultra Shift™ is recommended in applications where GM ® Part #12345349, GM ® Auto Trak II Part #1237508, Toyota LF 75W 08885-81080, Ford ® Part #D80Z19C547A & ESRY 19C547, Chrysler ® Part #4773167, or Mercedes Benz ® Part #900260315 are specified.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Clear** |
| Color | N/A | **Yellow** |
| Odor | N/A | **Sulfur** |
| Density (g/mL) | D4052 | **0.83** |
| Density, U.S. (lbs/gal), calculated | N/A | **6.9** |
| Viscosity @ 100°C, cSt | D445 | **~9.7** |
| Viscosity @ 40°C, cSt | D445 | **~49** |
| Flash Point °F (PMCC) | D93 | **>211** |
| Brookfield Viscosity @ -40°C, cPs | D2983 | **21,795** |

## 04 // APPLICATION

Use quantity in accordance with vehicle manufacturer's recommendations.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **1 qt.** | 12 | 24 lbs. |