AUTOMOTIVE BUFFING COMPOUND
PRODUCT PERFORMANCE & DATA SHEET

#3100

MAGNA BUFF



01 // OUTSTANDING FEATURES

- Designed for use on base-coat/clearcoat finishes.
- Repairs factory-paint imperfections.
- Excellent for removing wet-sanding marks on new paint.

02 // DESCRIPTION

A semi-viscous, cream designed specifically as a buffing compound for basecoat clearcoat systems and is body shop safe. It removes heavy scratches, blemishes, and factory-paint defects on basecoat clearcoat painted finishes. For best results, Magna Buff® should be followed with a glaze.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Viscous Liquid**
Color	N/A	**Blue**
Odor	N/A	**Solvent**
Density, U.S. (lbs/gal) @ 68°F	D1475	**~9.0**
Solids, %	E1868	**~25**
Viscosity, Brookfield, cPs	N/A	**~30,000**
Body Shop Safe	N/A	**Yes**
VOC Complaint	N/A	**Yes**
Biodegradable	N/A	**No**

04 // APPLICATION

Directions: For best results, surface should be clean, cool and out of direct sunlight. Shake container well before using. Note: applying excessive pressure while buffing may lead to "burning" or permanent damage to the paint. Hand use: Apply a generous amount of Magna Buff ® onto a soft cloth and apply to small sections of paint using medium pressure in an overlapping, Circular motion until scratches and blemishes disappear. Machine use: Apply Magna Buff ® to the painted Surface and buff while product is wet using a High-speed polisher and wool pad (do not exceed 2000 rpm) or flex polisher and foam pad (speed: 6). Repeat until surface imperfections are removed

05 // PACKAGING

FILL	CASE QTY	CASE WT
1 gal.	4	39 lbs.