**AUTOMOTIVE SHAMPOO**
PRODUCT PERFORMANCE & DATA SHEET

**#6272**

# W.W SPECIAL




## 01 // OUTSTANDING FEATURES

- A concentrated liquid soap
- Leaves a waxy feel on the surface
- Thin enough for a pressure-wash system.

**Performance ratings // Foaming 7 // Concentration 6**

## 02 // DESCRIPTION

A shampoo formulated to produce high foam & remove the toughest road film and soil while leaving behind a waxy shine. Works well on cars, trucks, boats, & RVs.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Viscous Liquid** |
| Color Odor | N/A | **RED** |
| Density, U.S. (lbs/gal) @ 68°F | D4052 | **~8.60** |
| RI | N/A | **~9.0** |
| pH | E70 | **~11.5** |
| Viscosity, Brookfield, cP | N/A | **~1750** |
| Body Shop Safe | N/A | **Yes** |
| VOC Compliant | N/A | **Yes** |
| Biodegradable | N/A | **Yes** |

## 04 // APPLICATION

DIRECTIONS: FOR BEST RESULTS, SURFACE SHOULD BE COOL AND OUT OF DIRECT SUNLIGHT.

1. Dilute 3 ounces of product with 1 gallon of water.
2. Rinse exterior of vehicle thoroughly.
3. Apply diluted solution generously with a wash mitt, soft cloth, or pressure wash system.
4. Rinse well with clean water.
5. Thoroughly dry vehicle with either a clean chamois or clean, soft towel. As with any car polish, wax or sealant, pre-test on an inconspicuous area prior to applying to entire section.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **5 gal** | 1 | 47 lbs |
| **55 gal** | 1 | 495 lbs |