**#0136**

# A/C QUIET MAX




## 01 // OUTSTANDING FEATURES

- Compatible with R-12, R-134a and R-1234yf refrigerant.
- Compatible with and suitable for use in systems that contain ester, paraffin, PAO, POE and PAG oils.
- Compatible with air-conditioning system components. (Based on Sealed Tube Test compliant with ASHRAE 97 standard).
- Helps prevent corrosion, icing, and acid formation by forming a barrier to moisture.
- Contains a unique color dye for detecting leaks (under black light).

## 02 // DESCRIPTION

A universal lubricant for automotive air-conditioning systems that utilize R-134a, R-1234yf and R-12 refrigerant. The advanced formula is designed to lower operating temperature and wear, increase operational reliability, and reduce noise and energy consumption. Unlike other oils, A/C Quiet™ MAX is not hygroscopic and will not absorb moisture from the ambient air. Therefore, humidity-related problems such as icing on components or the formation of acids can be prevented with use of A/C Quiet™ MAX. It is scientifically designed to minimize the volume of oil that circulates with the refrigerant and maximize the amount that stays in the compressor where it is needed most.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Oil** |
| Color | N/A | **Amber** |
| Odor | N/A | **Characteristic** |
| Density (g/mL) | D4052 | **0.85** |
| Density, U.S. (lbs/gal), calculated | D1250 | **7.09** |
| Flash Point (°F) COC | ISO 2592 | **482** |
| Kinematic Viscosity, 40°C, cSt | DIN 51562 | **69** |

## 04 // APPLICATION

A/C Quiet™ MAX (#01361 and #01368): Add appropriate amount of A/C Quiet™ MAx to an air-conditioner system using MOC® A/C Injector Tool #76004. Follow A/C system manufacturer's instructions for charging of the system. Note: #01361 (2 oz.) is typically added if the refrigerant/oil level is low if the compressor is noisy and as a preventative maintenance step. Note: #01368 (8 oz.) Is typically added when installing a new A/C unit, retrofitting from R12 to R134a and to detect system leaks.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **01361 2 oz.** | 24 | 4 lbs. |
| **01368 8 oz.** | 24 | 5.5 lbs. |