#0437

CAT & O2 SENSOR CLEANER



01 // OUTSTANDING FEATURES

- Can Improve Engine Performance
- Helps Keep Oxygen Sensor Clean
- Can Reduce Harmful Emissions
- Can Restore Fuel Efficiency & Engine Performance

02 // DESCRIPTION

Formulated to effectively remove oil deposits and unburned fuel particles from the catalytic convertor and oxygen sensor. Over time, soot and carbon deposits can build up in the exhaust system increasing fuel consumption & harmful emissions.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Liquid**
Color	N/A	**Colorless**
Odor	N/A	**Solvent**
Density (g/ml)	D4052	**0.81**
Density, U.S. (lbs/gal) calculated	N/A	**6.73**
Flash Point (°F / °C) based on components	N/A	**≥ 52 / 11**
VOC %	N/A	**~ 97**

04 // APPLICATION

DIRECTIONS Add contents to fuel tank to treat up to 18 gallons of gasoline. Do not attach any emissions analysis equipment to the exhaust until after the cleaning process. Start engine and allow it to reach operating temperature. Engine should be running with the emergency brake engaged and the transmission out of gear or in “Park.” Leave engine running while adding CAT Converter & O2 Sensor Cleaner to fuel tank. Allow vehicle to run for 15 minutes before turning off engine.

05 // PACKAGING

FILL	CASE QTY	CASE WT
10 oz.	24	15.4 lbs.