#0611

PREMIUM SYNTHETIC ATF - RED



01 // OUTSTANDING FEATURES

- Superior oxidation stability.
- Very good cold weather performance.
- Improved shear stability.
- Conditions seals and hoses.

02 // DESCRIPTION

Formulated to provide wear and rust protection, lubricity, good flow properties, excellent high and low temperature performance as well as stringent anti-shudder capability. This fluid is suitable for use in Ford, General Motors, Chrysler ATF+4, Allison C4, Volkswagen #G052 162A2, Audi, Volvo, Toyota (T-IV), Lexus, Honda Z1, Hyundai, Nissan (Matic-J), Infiniti, BMW, Mercedes Benz, and Jaguar.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Oil**
Color	N/A	**Red**
Odor	N/A	**Petroleum**
Specific Gravity @ 68°F	D4052	**~0.85**
Density, U.S. (lbs/gal) (Calculated)	N/A	**~7.09**
Viscosity, cSt @ 100°C	D445	**~7**
Viscosity, cSt @ 40°C	D445	**~38**
Viscosity Index	D 2270	**> 147**

04 // APPLICATION

MOC® Premium Synthetic ATF (#0611) must be used according to equipment manufacturer's recommendations. Do not use in transmissions which require CVT or Dexron VI fluid.

05 // PACKAGING

FILL	CASE QTY	CASE WT
1 gal.	4 Bottles	30 lbs.
3 gal.	2 Bottles	46 lbs.