**AUTOMOTIVE CLEANER / DEGREASER**
PRODUCT PERFORMANCE & DATA SHEET

**#4140**

# PURPLE STUFF




## 01 // OUTSTANDING FEATURES

- High-foaming cleaner that cleans concrete and degreases non-aluminum engines.
- An excellent all-around cleaner when diluted properly.
- Reduces the number of products needed in a shop.

## 02 // DESCRIPTION

A hot-type degreaser and floor cleaner well-suited for the toughest jobs. It works well on engines, tires, and floors.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Liquid** |
| Color | N/A | **Purple** |
| Odor | N/A | |
| Density, U.S. (lbs/gal) @ 68°F | D4052 | **1.04** |
| Density, U.S. (lbs/gal) @ 68°F (calculated) | N/A | **~8.7** |
| pH | E 70 | **≥ 13.0** |
| RI | N/A | **~18** |
| Body Shop Safe | N/A | **Yes** |
| VOC Complaint | N/A | **Yes** |
| Biodegradable | N/A | **No** |

## 04 // APPLICATION

Directions: Test product on an inconspicuous area for compatibility before using on entire surface. Avoid prolonged contact with aluminum, magnesium and painted surfaces. Can cause spotting or damage. Dilution: Always dilute with at least 12 parts water to 1 part product.

1. Use only in diluted form.
2. Spray or wipe diluted solution onto surface to be cleaned.
3. If needed, scrub surface with a brush or mop. Do not allow product to dry on surface.
4. Rinse surface thoroughly with water.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **1 gal** | 4 | 38 lbs. |
| **5 gal** | N/A | 47 lbs. |
| **55 gal** | N/A | 500 lbs. |