**#0105**

# DIESEL FUEL CONDITIONER




## 01 // OUTSTANDING FEATURES

- Formulated for all diesel fuel systems, including high pressure common-rail designs.
- **Cleans dirty injectors** // corrects problems that cause restricted spray patterns, poor fuel atomization, incomplete combustion and excessive emissions.
- Adds lubricity to reduce fuel-pump & injector wear caused by ULSD fuel.
- Raises the cetane number of diesel fuel for maximum horsepower, increased fuel economy and improved starting ability.
- Reduces smoke and engine knocking.

## 02 // DESCRIPTION

An advanced formula that removes deposits from fuel injectors, increases cetane levels and lubricates to restore horsepower, performance and fuel economy. It is designed to clean all types of heavy-and light-duty, off-road and marine diesel engines, including modern high-pressure common-rail designs. Excellent for use with ultra-lowsulfur diesel fuel (ULSD). Compatible with biodiesel and all types of exhaust emission systems, including diesel particulate filter (DPFs).

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Non-aqueous solution** |
| Color | N/A | **Clear light yellow** |
| Odor | N/A | **Petroleum** |
| Density (g/mL) | D4052 | **0.84** |
| Density, U.S. (lbs/gal), calculated | N/A | **7.00** |
| Flash Point (°F) Based on components | N/A | **149** |
| % VOC | N/A | **97** |

## 04 // APPLICATION

Add contents to the fuel tank at time of fill up. One 12 ounce bottle treats up to 20 gallons of fuel. For tools, equipment or recreational vehicles with 2 or 4 cycle engines, add ½ to 1 ounce of product per gallon of fuel.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **12 oz.** | 24 | 18 lbs. |