**#0149**

# LIMITED-SLIP CONCENTRATE




## 01 // OUTSTANDING FEATURES

- Enhances limited-slip performance (anti-chatter) of rear axles.
- Compatible with most conventional and synthetic gear oils.
- Eliminates the need for inventory multiple gear oils.

## 02 // DESCRIPTION

Designed to prevent chatter in limited-slip differentials and full-time four-wheel drive transfer cases. This product helps quiet gears in the differential and fortify standard gear lubricants. It is designed to be used with any GL-5 gear lubricant in Limited-slip applications. Recommended for rear-wheel drive passenger cars, trucks, and sport utility vehicles.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Clear & Bright** |
| Color | N/A | **Amber** |
| Odor | N/A | **Petroleum** |
| Density (g/mL) | D4052 | **0.91** |
| Density, U.S. (lbs/gal), calculated | N/A | **7.60** |
| Viscosity, cSt @ 100°C | D445 | **~7** |
| Viscosity, cSt @ 40°C | D445 | **~46** |
| Flash Point(°F), PMCC | D93 | **≥257** |

## 04 // APPLICATION

Add 1-part concentrate to every 25 parts of gear lubricant. Add treated gear lubricant to vehicle. Do not overfill system. For best results, use MOC® Limited-Slip Concentrate with MOC® Gear Guard™ #0148 or #0414 gear oil. Product may be added between services or as needed.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **4 oz.** | 12 | 4 lbs. |