#0411

MULTI-VEHICLE SYNTHETIC ATF



01 // OUTSTANDING FEATURES

- Full synthetic formula; not a synthetic blend.
- Highly resistant to shearing, oxidation and thermal breakdown.
- Provides excellent flow properties at low temperatures and film protection at high temperatures.
- Outstanding anti-wear properties to protect transmission parts.
- Optimizes Inventory by eliminating the need to stock different types/brands of ATF.
- Conditions seals and helps prevent leaks.

02 // DESCRIPTION

A special blend of fully synthetic base oils combined with a multi-functional additive system that provides superior anti-wear protection and performance in virtually all types of passenger and commercial automatic transmissions. It offers excellent high & low temperature fluidity, shear stability, seal protection and oxidation resistance. This premium formula may be used in place of synthetic fluids required or specified by a wide range of OEMs, including those used for extended drain and severe duty intervals. This product is designed to be used in conjunction with the MOC® ATF Fluid Exchanger #94500 & ATF Cleaner/Supplement Kit #01941..

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Clear**
Color	N/A	**Red**
Density (g/mL)	D4052	**0.85**
Density, U.S. (lbs/gal), calculated	N/A	**7.09**
Viscosity,cSt @ 40°C	D445	**~38**
Viscosity, cSt @ 100°C	D445	**~7.00**
Viscosity Index	N/A	**147**
Brookfield Viscosity @ -40°C, cP	N/A	**~13,000**
Pour Point °C	D97	**-40**
Flash Point °F	N/A	**419**

04 // APPLICATION

Use in automatic transmissions according to equipment manufacturer's recommendations. DO NOT use in transmissions that require CVT or Type F fluids.

05 // PACKAGING

FILL	CASE QTY	CASE WT
1 gal	4	30 lbs.
3 gal	2	46 lbs.
55 gal	1 Drum	415 lbs.