#0428

GEAR GUARD PLUS SAE 75W-140



01 // OUTSTANDING FEATURES

- Superior lubrication and protection for bearings and gears.
- Helps prevent wear, pitting, gear noise and corrosion under high-load conditions.
- Excellent fluidity and protection in extreme temperatures.
- Contains special additives to reduce chattering in limited- slip differentials.
- · Can be used in conventional differentials in addition to limited slip, avoiding the need for a supplement or application errors.
- Recommended for use where Ford M2C-192A, GM 12346140, Chrysler MS-8985, or GL-5 SAE 75W-140 gear oil is specified.

02 // DESCRIPTION

A multigrade synthetic (polyalphaolefin), A.P.I. GL-5 rated gear oil formulated to SAE 75W-140 viscosity. It is a premium extreme-pressure lubricant designed for use in axle applications requiring limited-slip performance but can also be used in conventional differentials. MOC® Gear Guard™ Plus SAE 75W-140 is a versatile product that can be used in place of 85w-140, SAE 140 oils and eliminates the need for supplemental friction modifiers such as Ford M2C118-A, Chrysler MS- 5630, or GM 1052358. It is designed to provide excellent extreme pressure protection, load carrying capacity, anti-foam performance, corrosion protection, and thermal stability protection.

03 // SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	N/A	**Oil**
Color	N/A	**Amber**
Odor	N/A	**Petroleum**
Density (g/mL) @68 °F	D4052	**0.87**
Density, U.S. (lbs/gal), calculated @68 °F	N/A	**7.26**
Viscosity @ 100°C, cSt	D445	**26.0**
Viscosity Index	D2270	**120 (typical)**
Brookfield Viscosity @ -40° C, cP	D2983	**100,000**

04 // APPLICATION

Follow vehicle manufacturer's recommendations for use of product. Gear Guard™ Plus is designed to be used in conjunction with MOC® Differential/Driveline service equipment and tools.

05 // PACKAGING

FILL	CASE QTY	CASE WT
1 quart	12 Bottles	24.14 lbs.
16 gal	1 drum	129.9 lbs.