**#16502**

# OPTIMIZER LIQUID




## 01 // OUTSTANDING FEATURES

- Loosens and removes stubborn carbon.
- Will not harm catalytic converter or oxygen sensor when used as directed.
- Restores engine performance.
- Designed for “hard-to-fix” problem areas.

## 02 // DESCRIPTION

A unique liquid cleaner designed to remove carbon and other deposits in the fuel induction system. The blend of solvents and cleaners is specifically designed to address “hard-to-fix” problem areas. Removing carbon from intake valves and combustion chambers can help eliminate cold-starts, hesitation and other drivability problems. The product contains no alcohol and will not harm seals, oxygen sensors or catalytic converters. When used as directed Optimizer™ (Non Aerosol) can be used on all gasoline or diesel engines. It is highly effective as a solution for carbon buildup problems on direct-injected engines.

## 03 // SPECIFICATIONS

| TEST | ASTM METHOD | TYPICAL RESULTS |
|---|---|---|
| Appearance | N/A | **Aqueous Emulsion** |
| Color | N/A | **Cloudy Amber** |
| Odor | N/A | **Solvent** |
| pH | N/A | **9.5 +/- 0.5** |
| Specific Gravity @ 68°F (liquid portion) | D1298 | **0.96** |
| Density, U.S. (lbs/gal) @ 68°F | D1250 | **8.01** |
| Flash point °F, PMCC | D 93 | **150** |
| % VOC | N/A | **50** |

## 04 // APPLICATION

Vehicle should be at operating temperature. Recommended Method: Follow instructions for use with #73400 EDR-3 Fuel Machine. Alternate Method:

1. Attach #74100 A.I.S. Tool to Air-Intake System at throttle body opening.
2. Pour Optimizer into canister of #72480 Deluxe Cleaner Application Tool II.
3. Attach outlet hose of Cleaner Application Tool to A.I.S. Tool.
4. Follow instructions for use with #72480 Deluxe Cleaner Application Tool II.

## 05 // PACKAGING

| FILL | CASE QTY | CASE WT |
|---|---|---|
| **16 oz** | 12 Cans | 14.372 lbs. |